



MPN: 694/12LSH-1.5

Product Name: 694/12LSH 1.5mm Black XLPE/SWA/Basec Cable 12-Core 1m

Brand: Commodity Cables

Category: Steel Wire Armoured (SWA)

Product Description: This product is cut to specification. Hence when ordering, a multiple of 1 needs to be entered.

Key Features:

- Cable Size: 1.5mm²
- Number of cores: 12
- CPR Compliant
- BASEC-Approved
- Material: LSHF

Specifications:

- Approximate Outer Diameter: 18.3mm
- Approx. Cable Weight Kg / Km: 641
- Minimum Bending Radius: 366mm
- Maximum Conductor DC Resistance at 20 °C Ω / Km: 12.1
- Conductor AC Resistance at Maximum Operating Temperature at 50Hz Ω / Km: 15.43
- Conductor Short Circuit Current for 1 second: 0.21
- Conductor: Stranded Plain Copper Conductor according to IEC 60228 Class 2 (Round Compacted for 10 & 16mm²)
- Insulation / Temperature: Cross Linked Polyethylene (XLPE) / 90°C
- Bedding Before Armouring: Low smoke Halogen Free / 90°C / Black

ETIM Class-9.0: Power cable < 1 kV, for flexible applications (EC003250)

Applications:

- For outdoor and indoor fixed installations and it's normally used for power distribution in urban networks and industrial plants.
- Suitable for laying underground directly or in ducts or on trays in free air.
- Industrial automation systems for control and instrumentation circuits
- Renewable energy projects such as solar farms and wind power installations
- Marine and offshore applications including shipbuilding and offshore platforms.
- Transportation infrastructure projects like railway networks, subway systems, and airports

Standards:

- BS 6724
- BS EN 60228



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!