



MPN: 6943XLH-2.5

Product Name: 6943XLH 2.5mm² Black PVC XLPE/SWA/Bassec Cable 3-Core 1m

Brand: Commodity Cables

Category: Steel Wire Armoured (SWA)

Product Description: This product is cut to specification. Hence when ordering, a multiple of 1 needs to be entered. Armoured cable made up of a black PVC sheathing for industrial wiring and mains distribution. Designed for installation in a variety of ways; including in duct, clipped directly to a surface, on tray, in basket or in free air. They may also be laid direct in ground in free draining soil or embedded in concrete.

Key Features:

- Cable Size: 2.5mm²
- No. of cores: 3
- CPR Compliant
- BASEC-Approved
- Material: PVC

Specifications:

- Designation voltage U0/U (kV) 0,6/1
- Diameter of conductor (mm): 2
- Maximum D.C. resistance at 20 °C (ohm/km) 7.41
- Short-circuit temperature (°C) 250

ETIM Class-9.0: Power cable < 1 kV, for fixed installations (EC003248)

ETIM Features:

- Conductor material: Copper (EV000138)
- Nominal cross-sectional area of conductor (mm²):2.5
- Number of cores:3
- Core colour: Black (EV000206)
- Sheath colour: Black (EV000206)

Applications:

- Power distribution in industrial facilities and commercial buildings
- Underground wiring in tunnels, subways, and mining operations
- Industrial automation systems in manufacturing plants and refineries
- Renewable energy projects such as solar farms and wind power plants
- Marine and offshore applications including shipbuilding and offshore platforms
- Infrastructure projects like railway networks, airports, and telecommunications installations

Standards:

- BS 5467



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!