



MPN: 6944XLH-1.5

Product Name: 6944XLH 1.5mm² Black PVC XLPE/SWA/Basec Cable 4-Core 1m

Brand: Commodity Cables

Category: Steel Wire Armoured (SWA)

Product Description: This product is cut to specification. Hence when ordering, a multiple of 1 needs to be entered. For industrial wiring and mains distribution. Designed for installation in duct, clipped directly to a surface, on tray, in basket or in free air, they may also be laid direct in ground in free draining soil or embedded in concrete.

Key Features:

- Cable Size: 1.5mm²
- Number of cores: 4
- CPR Compliant
- BASEC-Approved
- Material: PVC

Specifications:

- Approximate Outer Diameter Conductor: 12.1
- Approximate Cable Weight KG/KM: 290
- Conductor Max. AC Resistance at 90°C 0.6686 Ω/km
- Minimum Bending Radius: 97mm
- Maximum Conductor DC Resistance at 20 °C Ω / Km: 12.1
- Conductor AC Resistance at Maximum Operating Temperature at 50Hz: 15.43
- Conductor Short Circuit Current for 1 sec: 0.21 KA
- Voltage: 600/1000 (1200) V
- Insulation / Temperature: Cross Linked Polyethylene according to IEC 60502-1 (XLPE) / 90°C
- Bedding Before Armouring: PVC Sheathing Flame Retardant / 90°C / Black
- Armouring: Galvanized Steel Wires

ETIM Class-9.0: Power cable < 1 kV, for fixed installations (EC003248)

ETIM Features:

- Conductor material: Copper (EV000138)
- Nominal cross-sectional area of conductor (mm²):1.5
- Number of cores:4
- Core colour: Black (EV000206)
- Sheath colour: Black (EV000206)

Applications:

- For outdoor and indoor fixed installations and it's normally used for power distribution in urban networks and industrial plants.
- Suitable for laying underground directly or in ducts or on trays in free air.
- Industrial automation systems for control and instrumentation circuits
- Renewable energy projects such as solar farms and wind power installations
- Marine and offshore applications including shipbuilding and offshore platforms.
- Transportation infrastructure projects like railway networks, subway systems, and airports

Standards:

- BS 5467
- BS EN 60228



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!