

REXEL CABLE SOLUTIONS





MPN: 6242YH-1.5

Product Name: 6242YH 1.5mm² Grey PVC Basec 2-Core & Earth Cable

Brand: Commodity Cables

Category: Twin & Earth (6242)

Product Description: This product is packaged as 50m Reel. Hence when ordering, a multiple of 50 needs to be entered. Made up of a solid plain copper wire complete with PVC insulation and sheathing, suitable for dry and humid environments, both domestic and industrial. For static applications on flat surfaces, on brickwork, under plaster, in ducts or pipes. Not suitable

Key Features:

Cable Size: 1.5mm²

Colour: GreyNo. of cores: 2CPR CompliantBASEC-Approved

Material: PVC

Specifications:

Low Voltage Directive: 2014/35/EU

• RoHS Directive: 2011/65/EU

• Minimum installation temperature: 5°C

Max. short circuit temperature: 160°C

• Recommended maximum tensile stress: 50 N/mm²

ETIM Class-9.0: Power cable < 1 kV, for fixed installations (EC003248)

ETIM Features:

- Conductor material: Copper (EV000138)
- o Conductor surface: Bare (EV000899)
- Nominal cross-sectional area of conductor (mm²):1.5
- Conductor Diameter (mm):1.5
- Conductor category: Class 1 = solid (EV004199)
- Number of cores:2
- Core insulation material: Polyvinyl chloride (PVC) (EV000163)
- Core identification: Colour (EV000207)
- Core colour: Several (EV006439)
- Max. conductor temperature (°C):70
- Screen: NoDrain wire: Yes
- Protective barrier: None (EV000494)
- Sheath material: Polyvinyl chloride (PVC) (EV000163)
- o Sheath colour: Grey (EV000270)
- Oil resistant according to IEC 60811-404: No
- Low temperature resistant according to EN 60811-504+505+506: No
- Permitted cable outer temperature during assembling/handling (°C):0 60
- Nominal voltage U0 (V):300
- Nominal voltage U (V):500

Applications:

- Suitable for fixed installations in dry or damp premises
- Ideal for commercial and domestic applications

Standards:

- BS 6004
- EN 60228

