



MPN: 6243YH-1.5

Product Name: 6243YH 1.5mm² Grey PVC Basec 3-Core & Earth Cable

Brand: Commodity Cables

Category: 3 Core & Earth (6243)

Product Description: This product is packaged as 50m Reel. Hence when ordering, a multiple of 50 needs to be entered. Premium fire safety flat wiring cable with bare CPC.

Key Features:

- Cable Size: 1.5mm²
- Plain annealed copper conductors
- No. of cores: 3
- CPR Compliant
- BASEC-Approved
- Material: PVC

Specifications:

- Low Voltage Directive: 2014/35/EU
- RoHS Directive: 2011/65/EU
- Class of conductor: 1
- Maximum conductor resistance at 20oC (Ω / km): 12.1

ETIM Class-9.0: Power cable < 1 kV, for fixed installations (EC003248)

ETIM Features:

- Conductor material: Copper (EV000138)
- Conductor surface: Bare (EV000899)
- Nominal cross-sectional area of conductor (mm²):1.5
- Conductor Diameter (mm):1.5
- Conductor category: Class 1 = solid (EV004199)
- Number of cores:3
- Core insulation material: Polyvinyl chloride (PVC) (EV000163)
- Core identification: Colour (EV000207)
- Core colour: Several (EV006439)
- Max. conductor temperature (°C):70
- Screen: No
- Drain wire: Yes
- Protective barrier: None (EV000494)
- Sheath material: Polyvinyl chloride (PVC) (EV000163)
- Sheath colour: Grey (EV000270)
- Oil resistant according to IEC 60811-404: No
- Low temperature resistant according to EN 60811-504+505+506: No
- Permitted cable outer temperature during assembling/handling (°C):0 - 60
- Nominal voltage U₀ (V):300
- Nominal voltage U (V):500

Applications:

- Suitable for fixed installations in dry or damp premises
- Ideal for commercial and domestic applications

Standards:

- BS 6004
- EN 60228



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!