



MPN: 6945LSH-4.0

Product Name: 6945LSH-4.0 4.0m² Black LSZH/SWA/Basec Cable 5-Core 1m

Brand: Commodity Cables

Category: Steel Wire Armoured (SWA)

Product Description: This product is cut to specification. Hence when ordering, a multiple of 1 needs to be entered. Armoured Cable suitable for industrial wiring and mains distribution, where smoke and toxic emission would pose a major hazard in the event of fire. Suitable for laid direct in the ground, or in duct, clipped directly to a surface, on tray, in basket or in free air. May also be embedded in concrete.

Key Features:

- Cable Size: 4.0mm²
- No. of cores: 5
- CPR Compliant
- BASEC-Approved
- Material: LSZH

Specifications:

- Designation voltage U0/U (kV) 0,6/1
- Diameter of conductor (mm): 2.55
- Maximum D.C. resistance at 20 °C (ohm/km) 4.61
- Short-circuit temperature (°C) 250

ETIM Class-9.0: Power cable ≥ 1 kV, for fixed installations (EC003251)

ETIM Features:

- Conductor material: Copper (EV000138)
- Nominal cross-sectional area of conductor (mm²):4
- Conductor Diameter (mm):4
- Number of cores:5
- Core colour: Black (EV000206)
- Sheath colour: Black (EV000206)

Applications:

- Power distribution in buildings, industrial plants, and infrastructure projects
- Underground installations in ducts, tunnels, and direct burial applications
- Industrial automation systems for control and instrumentation circuits
- Renewable energy projects such as solar farms and wind power installations
- Marine and offshore applications including shipbuilding and offshore platforms.
- Transportation infrastructure projects like railway networks, subway systems, and airports

Standards:

- BS 6724



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!