

# REXEL CABLE SOLUTIONS





MPN: 6945LSH-6.0

Product Name: 6945LSH-6.0 6.0mm<sup>2</sup> Black LSZH/SWA/Basec Cable 5-Core 1m

**Brand:** Commodity Cables

**Category:** Steel Wire Armoured (SWA)

**Product Description:** This product is cut to specification. Hence when ordering, a multiple of 1 needs to be entered. Armoured Cable suitable for industrial wiring and mains distribution, where smoke and toxic emission would pose a major hazard in the event of fire. Suitable for laid direct in the ground, or in duct, clipped directly to a surface, on tray, in basket or in free air. May also be embedded in concrete.

### **Key Features:**

Cable Size: 6.0mm<sup>2</sup>

• No. of cores: 5

- CPR Compliant
- BASEC-Approved
- Material: LSZH

# **Specifications:**

- Designation voltage U0/U (kV) 0,6/1
- Diameter of conductor (mm): 3.1
- Maximum D.C. resistance at 20 °C (ohm/km) 3.08
- Short-circuit temperature (°C) 250

### **ETIM Class-9.0:** Power cable >= 1 kV, for fixed installations (EC003251)

#### **ETIM Features:**

- Conductor material: Copper (EV000138)
- o Conductor surface: Other (EV000154)
- Nominal cross-sectional area of conductor (mm²):6
- o Conductor Diameter (mm):6
- Conductor category: Class 2 = stranded (EV004200)
- Number of cores:5
- o Twisted cores: No
- Core insulation material: Other (EV000154)
- Core identification: Colour (EV000207)
- Core colour: Other (EV000154)
- Armouring/reinforcement: Lap-screen (EV004234)
- Sheath material: Other (EV000154)Sheath colour: Black (EV000206)

## **Applications:**

- Power distribution in buildings, industrial plants, and infrastructure projects
- Underground installations in ducts, tunnels, and direct burial applications
- Industrial automation systems for control and instrumentation circuits
- Renewable energy projects such as solar farms and wind power installations
- Marine and offshore applications including shipbuilding and offshore platforms.
- Transportation infrastructure projects like railway networks, subway systems, and airports

#### **Standards**:

BS 6724

