



MPN: 6944LSH-35.0

Product Name: 6944LSH 35.0mm² Black XLPE/SWA/Basec Cable 4-Core 1m

Brand: Commodity Cables

Category: Steel Wire Armoured (SWA)

Product Description: This product is cut to specification. Hence when ordering, a multiple of 1 needs to be entered. PX Manufacturing 6944LSH 25 SWA XLPE insulated LSOH sheathed armoured cable with copper conductor and 25mm² cross section area. Conductor is Class 2 stranded. Black in colour.

Key Features:

- Cable Size: 35.0mm²
- Number of cores: 4
- CPR Compliant
- BASEC-Approved
- Material: LSHF

Specifications:

- Conductor Operating Temp. up to 90 °C
- Conductor Short Circuit Temp. up to 250 °C
- Flame Retardant acc. to BS EN 60332-3-24
- Smoke emission acc. to BS EN 61034
- Acid gas emission acc. to BS EN 60754
- Conductor Max. DC Resistance at 20°C : 0.524 Ω/km
- Conductor Max. AC Resistance at 90°C: 0.6686 Ω/km
- Reactance at 50 Hz: 0.0799 Ω/km
- Conductor Short Circuit Current for 1 second: 5 kA
- Rated Current (laid in Air) *: 166 A
- Rated Current (laid in Duct) *: 140 A
- Rated Current (laid in Ground) *: 185 A
- Conductor: Circular Stranded Compacted Plain Annealed Copper (Class 2)
- Insulation: XLPE (GP 8)
- Inner Sheath: LSHF
- Nominal Cable Diameter: 30.25mm

ETIM Class-9.0: Power cable < 1 kV, for flexible applications (EC003250)

Applications:

- For outdoor and indoor fixed installations and it's normally used for power distribution in urban networks and industrial plants.
- Suitable for laying underground directly or in ducts or on trays in free air.
- Industrial automation systems for control and instrumentation circuits
- Renewable energy projects such as solar farms and wind power installations
- Marine and offshore applications including shipbuilding and offshore platforms.
- Transportation infrastructure projects like railway networks, subway systems, and airports

Standards:

- BS 6724
- BS EN 60228



Unlock exclusive deals and discover a world of innovative solutions by scanning our QR code and visiting Rexel's website today!