

technical hotline +44 (0)1268 563720

decorative | wiring devices

Satellite Socket Outlets

TWIN
OUTLET WITH
TV/FM DIPLEXER
FLUSH

SINGLE OUTLET
F TYPE
SATELLITE SOCKET
FLUSH

Floor Mounted Euro Frame

1 GANG STANDARD
FLOOR MOUNTED
EURO FRAME

1 GANG RECESS
FLOOR
MOUNTED EURO
FRAME

2 GANG
STANDARD
FLOOR
MOUNTED EURO
FRAME

2 GANG RECESS
FLOOR
MOUNTED EURO
FRAME



| | | | | | | | | | | | |
|----------|---|----------|---|--------|----|--------|----|--------|----|--------|----|
| K3582BSS | 5 | K3585BSS | 1 | 790BSS | 10 | 791BSS | 10 | 795BSS | 10 | 796BSS | 10 |
| K3582BRC | 5 | K3585BRC | 1 | 790BRC | 10 | 791BRC | 10 | 795BRC | 10 | 796BRC | 10 |
| K3582SAG | 5 | K3585SAG | 1 | 790SAG | 10 | 791SAG | 10 | 795SAG | 10 | 796SAG | 10 |
| K3582PCR | 5 | K3585PCR | 1 | | | | | | | | |

IEC 169-2: 1965

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

 BS 5733: 2010 where
applicable

FM diplexer for
connection to single
co-axial aerial lead
with combined TV & FM
signals. Suitable for
UHF TV and VHF FM
radio.

Fully screened
modular TV/
Satellite outlets
are available to fit
Euro frontplates.
See page 56 for
details.

MOUNTING BOXES:

 FLUSH:
1 GANG: 86ZIC
2 GANG: 88ZIC

Boxes must have a minimum depth of 35mm

 DIMENSIONS:
1 GANG: 102 x 86mm
2 GANG: 102 x 146mm

 FIXING CENTRES:
1 GANG: 60.3mm
2 GANG: 120.6mm

NOTE:

Recessed Euro Frame products must be used with 'F' Type
connectors. This ensures full lid closure when the aerial lead is
disconnected.

Power sockets must only be used with the standard Euro Frame
products as the recessed type may NOT allow full plug engagement.

BS 5733: 2010

For a complete selection of Euro modules, see pages 54-56.