

Nylon pull-wire fixed endings pulling eye and flexible head with pulling eye 10 m Ø 4 mm without reel

Suitable for passing the needle through unencumbered environments.



Characteristics

Biz references : **BIZ 700 810**

Length (m) : **10**

Pull-wire Ø (mm) : **4**

Breakage (kg) : **70**

Benefits

- Very flexible.
- Low shape memory.



GENERAL INFORMATION

Technical details

Hexagonal crimping of sleeves.

Included:

Flexible head with M5 threaded Ø 6 mm eyelet (BIZ 700 240).

M5 threaded Ø 6 mm eyelet (BIZ 700 241).

Advices

Maximum bending diameter, 4 cm.

Application(s)

For pulling cables through electrical conduits and ducts from 16 to 25 mm.

Ideal for pulls longer than 20 m.



LOGISTIC INFORMATION

Packaging



Color sticker

Height (cm) : 28

Length (cm) : 28

Depth (cm) : 2,3

Net weight (kg) : 0,162

Gross weight (kg) : 0,162



3 700882 122506

Outer package 1



x 60.00

Carton box

Height (cm) : 60

Length (cm) : 32

Depth (cm) : 32

Net weight (kg) : 9,72

Gross weight (kg) : 9,7



3 700882 131102

Outer package 2



x 720.00

Pallet

Height (cm) : 113

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 116,64

Gross weight (kg) : 116,6



3 700882 131140