

Pullwire polyester mono 25 m Ø 3 mm with dispenser

The go anywhere residential wire-pulling needle!



Caracteristics

Length (m) : 25
Pull-wire Ø (mm) : 3
Breakage (kg) : 80

Benefits

- Highly rigid.
- No shape memory.
- Does not rotate on its axis.
- Ultra-slim diameter.



GENERAL INFORMATION

Technical details

Hexagonal crimping of sleeves.

Includes:

Flexible head with crimped M5 Ø 6 mm eyelet (BIZ 700 240).

M5 threaded Ø 6 mm eyelet (BIZ 700 241).

Casing (BIZ 760 058).

Advices

Maximum bending diameter, 2 cm.

Application(s)

For pulling cables through 16 to 50 mm electrical ducts and conduits, even if congested and curved.

Ideal for distances up to 15 m.



LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 8

Length (cm) : 36

Depth (cm) : 30

Net weight (kg) : 1,25

Gross weight (kg) : 1,25



3 781395 102412

Outer package 1



x 4.00

Carton box

Height (cm) : 35

Length (cm) : 39

Depth (cm) : 32

Net weight (kg) : 5

Gross weight (kg) : 5,65



3 781395 104058

Outer package 2



x 72.00

Pallet

Height (cm) : 119

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 90

Gross weight (kg) : 116,7



3 781395 104201