

Pullwire polyester mono 30 m Ø 4.5 mm with reel

The compromise between flexibility and rigidity!



Caracteristics

Length (m) : **30**
 Thread type : **M5**
 Pull-wire Ø (mm) : **4.5**
 Breakage (kg) : **140**

Benefits

- Highly rigid.
- No shape memory.
- Does not rotate on its axis.
- Long lifetime.

GENERAL INFORMATION

Technical details

Hexagonal crimping of sleeves.
 Includes:
 Flexible head with M5 threaded Ø 6 mm eyelet (BIZ 700 240).
 M5 threaded Ø 6 mm eyelet (BIZ 700 241).
 Casing (BIZ 760 058).

Advices

Maximum bending diameter, 4 cm.

Application(s)

For pulling cables in 16 to 50 mm ducts, even congested and curved ones.
 Ideal for pulling cables in varied environments up to 30 m.

LOGISTIC INFORMATION

Packaging



No packaging

Height (cm) : 8
 Length (cm) : 36
 Depth (cm) : 30
 Net weight (kg) : 1,53
 Gross weight (kg) : 1,53



3 701395 102429

Outer package 1



x 4.00

Carton box

Height (cm) : 35
 Length (cm) : 39
 Depth (cm) : 32
 Net weight (kg) : 6,12
 Gross weight (kg) : 6,77



3 701395 104065

Outer package 2



x 72.00

Pallet

Height (cm) : 119
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 110,16
 Gross weight (kg) : 136,86



3 701395 104218