

Pullwire polyester 30 m Ø 4.5 mm with carter

The compromise between flexibility and twisting strength!



Caracteristics

Length (m) : **30**
Thread type : **M5**
Pull-wire Ø (mm) : **4.5**
Breakage (kg) : **150**

Benefits

- Excellent performance.
- No shape memory.
- Long lifetime.



GENERAL INFORMATION

■ Technical details

Triple twisted polyester.
Hexagonal crimping of sleeves.
Included:
Flexible head with M5 threaded Ø 6 mm eyelet (BIZ 700 240).
M5 threaded Ø 6 mm eyelet (BIZ 700 241).
Includes casing (BIZ 760 058).

■ Advices

Maximum bending diameter, 3 cm.

■ Application(s)

For pulling cables through ducts of diameter 20 to 50 mm, even when congested.
Ideal for distances of up to 30 m.



LOGISTIC INFORMATION

 Packaging**No packaging**

Height (cm) : 8

Length (cm) : 36

Depth (cm) : 30

Net weight (kg) : 1,58

Gross weight (kg) : 1,58



3 701395 102450

 Outer package 1

x 4.00

Carton box

Height (cm) : 35

Length (cm) : 39

Depth (cm) : 32

Net weight (kg) : 6,32

Gross weight (kg) : 6,97



3 701395 104096

 Outer package 2

x 72.00

Pallet

Height (cm) : 119

Length (cm) : 120

Depth (cm) : 80

Net weight (kg) : 113,76

Gross weight (kg) : 140,46



3 701395 104249