



# 25 m Ø 3 mm fiberglass pullwire with reel

*Perfect for passing through long, straight ducts and conduits.*



## Characteristics

- Length (m) : 25
- Thread type : M5
- Pull-wire Ø (mm) : 3
- Breakage (kg) : 70

## Benefits

- Very rigid.
- No friction points.
- Does not rotate on its axis.

## GENERAL INFORMATION

### Technical details

Hexagonal crimping of sleeves.  
Included:  
Flexible head with M5 threaded Ø 6 mm eyelet (BIZ 700 240).  
M5 threaded Ø 6 mm eyelet (BIZ 700 241).  
Casing (BIZ 760 058).

### Advices

Maximum bending diameter, 6 cm.

### Application(s)

For pulling cables through electrical conduits and ducts from 16 to 50 mm.  
Ideal for long pulls with few curves.

## LOGISTIC INFORMATION

### Packaging



#### No packaging

Height (cm) : 8  
Length (cm) : 36  
Depth (cm) : 30  
Net weight (kg) : 1,2  
Gross weight (kg) : 1,2



### Outer package 1



#### Carton box

Height (cm) : 35  
Length (cm) : 39  
Depth (cm) : 32  
Net weight (kg) : 4,8  
Gross weight (kg) : 5,45

x 4.00



### Outer package 2



#### Pallet

Height (cm) : 119  
Length (cm) : 120  
Depth (cm) : 80  
Net weight (kg) : 86,4  
Gross weight (kg) : 113,1



x 72.00