

Benchmark**BMG745**

CUT D HIGH STRENGTH NYLON / PU GLOVE

A dexterous high cut resistance glove, glass and steel fibre free. Ideal in dry or greasy conditions.

FEATURES

- › Cut resistance: Level D (EN 388:2016)
- › A flexible and comfortable glove offering great dexterity
- › Glass and steel fibre free reduce risks of irritation
- › Durable polyurethane palm coating ensures good protection against abrasion
- › Flexible, close-fitting design for a comfortable wearing experience
- › Breathable back of hand to reduce perspiration
- › Seamless knit prevents irritation
- › Elasticated wrist provides a secure fit



SUITABLE FOR

Typical Industries

- Aerospace
- Engineering
- Automotive
- Logistics
- Construction
- Manufacturing

Suitable Applications

- Assembly
- Handling sharp parts
- Maintenance
- Goods handling

CERTIFICATION



EN 388:2016



4X42D

ASTM / ANSI
105-2016

CUT

See overleaf for explanation

Benchmark**BMG745****PRODUCT INFORMATION**

MATERIALS	LINER:	13 gauge high strength nylon
	COATING:	Polyurethane
COLOUR	Grey/Black	
LENGTH (mm)	250 (Size Dependent)	
CUFF STYLE	Elasticated knit wrist	

RECOMMENDATIONS FOR USE

- **USE:** General handling glove with cut protection. Not suitable for thermal, electrical and chemical protection. Do not use near moving machines if there is a risk of entanglement
- **STORAGE:** Store in dry conditions in the original packaging and away from direct sunlight
- **CLEANING:** To clean, wipe with a damp cloth. Note: The performance characteristics of worn and laundered gloves may differ from the results shown. Inspect the gloves to ensure no damage is present.
- **LIFETIME:** Service life depends on the glove application and therefore cannot be specified. It is the responsibility of user to ensure the glove is suitable for its intended use.

ORDERING DETAILS

SIZE	CODE	PACKAGING
6/XS	BMG00745FB	10 pairs per bag
7/S	BMG00745FD	120 pairs per case
8/M	BMG00745FF	
9/L	BMG00745FH	
10/XL	BMG00745FJ	
11/XXL	BMG00745FL	

CERTIFICATION LEGENDS

MECHANICAL HAZARDS EN 388:2016
PERFORMANCE LEVELS*

0-4	0-5	0-4	0-4	A-F	P
Abrasion Resistance		Circular Blade Cut Resistance		Puncture Resistance	Impact Resistance
				Straight Blade Cut Resistance (EN ISO: 13997)	

*If tests are not performed or are not applicable, 'X' will be placed instead of a number/letter

EUROPE

www.globus.co.uk

E: sales@globus.co.uk

T: +44 (0)161 877 4747

F: +44 (0)161 877 4746

MIDDLE EAST AND AFRICA

www.globusgroup.com/gcc

E: gcc@globusgroup.com

T: +971 4 882 9962

F: +971 4 882 9963



Globus (Shetland) Ltd, T2 Trafford Point, Twining Road, Trafford Park, Manchester, M17 1SH, UNITED KINGDOM
Globus EMEA FZE, Jafza One, Tower A, Office 2201, Jebel Ali, PO Box 61195, Dubai, UNITED ARAB EMIRATES

©2021 Globus (Shetland) Ltd | BMK-DATA-BMG745_0521_2