

Product Data Sheet



ELECTRAK

Electrak 25 Low Noise Underfloor Busbar 2 Pole + Earth + Clean Earth 13A Fused High Integrity Tap-Off 3m

REF. JP2327 | EAN. 5012774028987

> [Link to e-catalog product sheet](#)

Product description

- Tap-off length is determined by the cable and not the conduit length, e.g. a 3m tap-off has 3m of cable and 2.6m of flexible metal conduit
- Tap-off units in excess of 3m should only be used if they contain a fuse or if the powertrack is protected by a protective device not exceeding 32A

Technical characteristics

Number of conductors (without earthing)	2
Number of poles	2
Rated current AC 50 Hz	13 A
Rated voltage AC 50 Hz	230-400 V
Phase selection	No
With locking	Yes
Branch off type	Pipe in-lead
Number of CEE socket outlets	0
Number of NEMA socket outlets	0

Number of other socket outlets	0
Protection	Cylindrical fuse
Colour	Other
RAL-number	6029
Degree of protection (IP)	IP40
Length	3000 mm
Width	75 mm
Height	43 mm

Documents

Catalogue pages

- powering-the-workplace-2023-011.pdf | PDF (0.2Mo)
- powering-the-workplace-2023-008-009.pdf | PDF (0.88Mo)