

62BBSK

**Busbar clamps and sockets – 100–200A Busbars**

Type	Nominal rating, I _e (A)	Bore diameter mm	Capacity mm ²	Eaton list number	mm	Bolt Size
U-Clamps	20–63	—	25	2 BBCL	19	M6
	63–100	—	70	3 BBCL	22	M8
	100–200	—	120	6 BBCL	38	—

Busbar clamps and lugs connection – 400–800A Busbars

Type	Nominal rating, I _e (A)	Bore diameter mm	Capacity mm ²	Eaton list number	mm	Bolt Size
U-Clamps	20–63	—	25	4 BBCL	19	M6
	63–100	—	70	5 BBCL	22	M8
	100–200	—	120	6 BBCL	38	—
Lugs connection	315–400	22.5	240	82 BBSK	133	M14

21BBMS

**Switchgear mounting sets**

Description	Nominal rating, I _e (A)	Eaton list number
Exel Switch-disconnector-fuses/ Switch-disconnectors	20, 32	11 BBMS
	63, 100, 125	21 BBMS
Glasgow Fuse-switch-disconnectors/ Switch-disconnectors	63, 100	31 BBMS
	200	41 BBMS
	400	51 BBMS
	630, 800	61 BBMS

- The difference between 2BBCL/4BBCL is the bolt length(30mm and 50mm respectively).
- The difference between 3BBCL/5BBCL is the bolt length(40mm and 55mm respectively).