



GL019 SQ

1W square mini LED ground light

FEATURES

Wattage	1W (350mA) 2W (700mA)
IP rating	IP68
IK rating	IK07
Colour flexibility	Fixed colour
Walk over / drive over	Walk over (5mm toughened glass)
Input	350mA / 700mA
LED lifetime	70,000h L70, B10
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 33mm
Bathroom zone	0
Inrush current	N/A
Construction material	Stainless steel (316)
Weight	134g
Maximum ambient temperature	35°C
SELV	N/A
Electric class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	350mA			700mA		
				lm	lm/W	lx at 1m	lm	lm/W	lx at 1m
GL019 SQ F NW	4000K	20°	>80Ra	90	90	396	130	65	572
GL019 SQ S NW	4000K	12°	>80Ra	90	90	1833	130	65	2648
GL019 SQ F WW	3000K	20°	>80Ra	80	80	353	125	63	551
GL019 SQ F BLUE	Blue	20°	-	10	10	44	20	10	88
GL019 SQ S BLUE	Blue	12°	-	10	10	204	20	10	407

WIRING INFORMATION

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLD UNI-DRIVE 350MA	N/A	Yes	Yes (1-10V)	1	1	10
PLU/700 3-9	N/A	Yes	No	1	3	9

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold separately	422-423
TUBE332	Installation tube	Sold separately	236
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422

Ground lights.

01604 495 151
collingwoodlighting.com

@collingwoodLED

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

New - can now also be used with a 700mA driver for increased light output (see page 282 for driver matrix)

Shallow depth for easy installation

Square fascia for a different decorative effect

350mA or 700mA driver available

Beam angle: 12° 20°

