



GL022

Square 30° slotted LED ground / step light

FEATURES

Wattage	1W
IP rating	IP68
IK rating	IK07
Colour flexibility	Fixed colour
Walk over / drive over	Walk over (5mm toughened glass)
Input	350mA
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 50mm
Bathroom zone	0
Inrush current	N/A
Construction material	Stainless steel (316)
Weight	400g
Maximum ambient temperature	35°C
SELV	N/A
Electric class [1, 2, 3]	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
GL022 NW	4000K	30°	>80Ra	10	10	10
GL022 WW	3000K	30°	>80Ra	8	8	8
GL022 27	2700K	30°	>80Ra	8	8	7
GL022 BLUE	Blue	30°	-	-	-	-

WIRING INFORMATION

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220-240V	Yes	No	1	1	9
PLR/350 1-5	220-240V	Yes	No	0	1	5
PLD UNI-DRIVE 350MA	220-240V	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

JB2 / JB4 / JB6	IP68 waterproof connectors	Sold separately	422-423
TUBE/50	Installation tube	Sold separately	236
WCR 275 BLACK	2-core rubber cable	Sold separately	423
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422

Step lights.

01604 495 151
collingwoodlighting.com

@collingwoodLED

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Angled light, ideal for use as a step light

Cast stainless steel for aged effect

Robust cable for outdoor use

Plane: C0/C180 C90/C270

