

Conduit - PVC Round Accessories

Description	distribution box
	Circular box for surface installation with 2 mounting lugs, standard mounting screw spacing 50.8mm (2") for conduit diameters 20mm to 25mm, with brass inserts M 4, without lid
Colour	white, similar to RAL 9010
Classification	IP30



Standard: BS 4607/5



Working temperature	Degree of protection (IP)	UV-Level*
-5 to +60°C	IP3X	L2

Part No.	Dimensions Ø/LxW x D	For tube diameter	ps	pl
NLRCA26	65 x 32 mm	20 mm	25 pc	240 pc
NLRCA56	65 x 32 mm	25 mm	20 pc	200 pc

Further technical details

Details	
Halogen free	False
Tackable	False
Number of inlets	2
Type of housing feed-through	Pipe socket
Equipped with	None
Cover model	Mounting cover
Explosion-tested version	False
Weatherproof	False
Material	PVC

*) L1: Indoor use - to avoid UV discoloration (no exposure to direct sunlight).

L2: Partially shaded: Outside, in areas with sun only for two to four hours a day, in shadowy places.

L3: Full sun: To be used also in areas with whole-day exposure to sunlight, e. g. roofs, antenna poles or PV panels.

Civil engineering and road construction products marked "L2" have to be laid in the shortest time possible to ensure colour fastness and stability.