

# Multi Socket Outlet - 2 Gang

## 653240/WT

16A

110v

2P+PE

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Ampere                           | 16A                                                                                   |
| Poles                            | 3P (2P+PE)                                                                            |
| Earth 'Clock' Position           | 4h                                                                                    |
| Voltage                          | 100 - 130V~                                                                           |
| Frequency                        | 50/60Hz                                                                               |
| Ingress Protection               | IP67 Socket Mounted on IP66 Enclosure                                                 |
| Colour Code                      | Hinged Lid Yellow RAL 1012<br>Bayonet Ring Grey RAL 7035<br>Enclosure Grey RAL 7035   |
| Connection Design                | Pre-Wired to Terminal Block                                                           |
| Contact                          | Contacts are brass                                                                    |
| Weight/pcs                       | .58 KG                                                                                |
| Packaging Unit                   | 1 pc                                                                                  |
| Material of Enclosure            | Plastic                                                                               |
| Protective Device                | None                                                                                  |
| Max Conductor                    | 10 mm <sup>2</sup>                                                                    |
| Cable Entry                      | Plain Side                                                                            |
| Additional Technical Information | Angled sockets fitted as standard - Straight sockets can be fitted on special request |
| Dimensions                       | 105(h) x 180(w) x 130(d) mm                                                           |



*\*All images used for illustrative purposes only*