

Sounder indicators

In areas which do not have to meet the new regulations regarding EN54-23 visual alarm devices, our range of sounder indicators can still provide excellent sound quality and light indication.

Xenon sounder indicator

FL-RL-R-S




Weatherproof Xenon sounder indicator


FL-RL-R-D



Dimensions



Xenon sounder indicator



Weatherproof xenon sounder indicator

Typical applications:

In regions where the EN54-23 VADs standard is not a requirement, the xenon sounder indicator provides an alternative option to the xenon indicator - where an audible warning is required in addition to light indication.

Typical applications:

The weatherproof version of the sounder indicator is IP65 rated which allows for installation in harsher environments.

Description	Dia (mm)	D (mm)
Xenon sounder indicator	93	92
Weatherproof xenon sounder indicator	93	121

Sound output

XENON sounder indicator, FL-RL-R-S/FL-RL-R-D	
Sound output	101dB(a) at 24V dc (typical tone 3)
Tones	32

Note: From 31st December 2013 a new beacon standard, EN 54-23 became mandatory across Europe where Construction Product Regulation (CPR) applies. If you are in a region where this standard applies please understand that these indicators do not meet the requirements of the new standards - **see p78 for compliant beacons and sounder beacons**

Catalogue numbers

Description	Code
FL-RL-R-S Conventional xenon sounder indicator	640001FULL0003X
FL-RL-R-D Weatherproof IP65 xenon sounder indicator	640031FULL0111X