



LEDLINE MAINS 400 45°

45° straight to mains wall washing light bar

FEATURES

Wattage	19W
IP rating	IP65
IK rating	IK02
Colour flexibility	Fixed colour
Tilttable	180°
Input	Mains AC
LED lifetime	70,000h L70 B50
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush current	2.1A 0.1ms
Construction material	Anodised aluminium
Weight	1.4kg
Maximum ambient temperature	35°C
SELV	Yes
Electric class [1, 2, 3]	1

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
ULM347M40	4000K	45°	>80Ra	1020	54	2366
ULM347M30	3000K	45°	>80Ra	1000	53	2320
ULM347M27	2700K	45°	>80Ra	970	51	2250

WIRING INFORMATION

Cable / flying lead	3m (H05RN-F) rubberised cable (outside diameter: 7mm)
Type of wiring required	Parallel

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	-	-

ACCESSORIES

ULBRACKET	2-piece black anodised aluminium bracket	Sold separately	277
-----------	--	-----------------	-----

Uplights.

01604 495 151
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

45° beam angle ideal for mid-level wall wash

Mains driver built-in for quick installation

Robust cable for permanent use outdoors

Beam angle: 45°

