

DIMMER COMPATIBILITY GlowDim

BASIC INFORMATION:

1. WHAT IS THE PRODUCT CODE AND WHERE DO I FIND IT?

The product code describes the lamp type. It contains 7 letters and digits and is starting with "A". Below an example for the product code of the stamp of the lamp:



220-240V **AC01770** 2700K
13 W 50/60 Hz 27 mA
Made in Germany XXX-XXXX

2. HOW CAN I READ THE FOLLOWING CHARTS?

Legend:
Information about the dimmability of the lamps. Green means very good dimmability, yellow means limited dimmability, red means undesired dimmability etc.

List of dimmers tested in laboratory conditions

Legend				
Very good dimmability with indicated number of lamps (dimming range greater than 75%)				
Limited dimmability with indicated number of lamps (dimming range smaller than 75%)				
Undesired dimmability				
Not relevant				
Not tested				

Dimmer				
Brand	Model	Voltage range	Power	Type
ABB	STD 50-3	230V50Hz	60-500	L
Altenburger Electronic	50.30	230V50Hz	15-350	T
ALPORA	DSP 400	230V50Hz	400	L
Berker	2861	230V50Hz	50-420	U
Bticino	LNNT441N	230V50Hz		
Bticino	LNNT4408	230V50Hz		
Bticino	NT4402N	230V50Hz	500	R
Busch-Jaeger	6513 U-102	230V50Hz	40-420	T
Busch-Jaeger	6523 U-102	230V50Hz	420	L
Busch-Jaeger	2250 U	230V50Hz	60-600	L
Busch-Jaeger	6526 U	230V50Hz		
Busch-Jaeger	2247 U-500	230V50Hz		
CENTURY CONTROL	MULTI DIMMER	230V50Hz	60-600	L
DINUY	RE EL1LE1	230V50Hz	400	LED
ELKO	400GLI	230V50Hz		
ELKO	315GLE	230V50Hz	20-315	T
ELKO	600GLI	230V50Hz	40-600	U
ELKO	420GLEI	230V50Hz	40-420	U

SUPERSTAR PAR16 35 36"		SUPERSTAR PAR16 50 36"		SUPERSTAR PAR16 80 36"		SUPERSTAR PAR16 80 120"	
							
EAN/Basic Code		EAN/Basic Code		EAN/Basic Code		EAN/Basic Code	
4052839330153/AC01184		4052839330178/AC01187		4052839330218/AB41905		405807503688/AC03043	
4052839330157/AC01192		4052839330195/AC01194		4052839330232/AB41906		405807503682/AC03051	
Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range	Number of Lamps	Dimming range
1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%
2-20	98% - 15%	2-20	97% - 12%	2-20	98% - 16%	2-20	98% - 16%
1-10	98% - 15%	2-10	97% - 1%	1-4	96% - 1%	1-4	96% - 1%
1-20	98% - 27%	1-20	98% - 26%	1-20	97% - 27%	1-20	97% - 27%
1-15	98% - 1%	1-10	97% - 5%	1-6	94% - 7%	1-6	94% - 7%
2-20	98% - 1%	2-9	98% - 1%	1-6	97% - 9%	1-6	97% - 9%
3-19	99% - 19%	2-12	97% - 19%	1-8	95% - 22%	1-8	95% - 22%
2-20	99% - 15%	2-20	98% - 17%	2-20	98% - 21%	2-20	98% - 21%
1-10	96% - 22%	1-10	97% - 26%				
1-10	98% - 16%	2-14	98% - 16%	1-9	97% - 15%	1-9	97% - 15%
1-13	98% - 34%	1-10	97% - 35%	1-5	97% - 15%	1-5	97% - 15%
1-20	98% - 15%	1-13	98% - 20%	1-8	97% - 23%	1-8	97% - 23%
2-13	98% - 1%	1-10	98% - 5%	1-6	97% - 9%	1-6	97% - 9%
1-11	98% - 1%	1-10	99% - 1%	1-5	99% - 7%	1-5	99% - 7%
1-10	98% - 1%	1-10	97% - 1%	1-4	97% - 1%	1-4	97% - 1%
2-20	98% - 6%	1-20	98% - 7%	1-20	97% - 10%	1-20	97% - 10%
1-20	98% - 1%	1-13	97% - 1%	1-8	96% - 1%	1-8	96% - 1%
1-14	98% - 1%	1-13	97% - 4%	1-10	97% - 19%	1-10	97% - 19%

Information about the OSRAM lamp type

Assessment of the results into categories. Includes the number of lamps and the related dimming range

DIMMER KOMPATIBILITÄT GlowDim

Legend					PARATHOM+ MR16 35 GLOWdim 36**		PARATHOM+ PAR16 50 GLOWdim 36°		PARATHOM+ CL A 40 GLOWdim		PARATHOM+ CL A 60 GLOWdim		PARATHOM+ CL B / BA GLOWdim		PARATHOM+ CL P GLOWdim		PARATHOM+ Globe GLOWdim		PARATHOM PRO AR111 GLOWdim*	
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)																			
	Limited dimmability with indicated number of lamps (dimming range smaler than 75%)				EAN / Basic Code		EAN / Basic Code				EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
	Undesired dimmability																			
	Not relevant																			
	Not tested				4058075052802 / AC03896		4058075052826 / AC03897		4058075808539 / AC02140		4058075801417 / AC02143		4058075808157 / AC02154 4058075815056 / AC02155		4058075809062 / AC02228		4058075808959 / AC02157		4058075812857 / AC02488 4058075812932 / AC02489	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 5 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type																
ABB	STD 50-3	230/50Hz	60-500	L					99 - 23%	97 - 27%	81 - 21%	96 - 24%	99 - 25%	94 - 26%	99 - 25%	94 - 26%	81 - 21%	96 - 24%	83 - 1%	101 - 1%
Altenburger Electronic	50.30	230/50Hz	15-350	T					77 - 29%	99 - 14%	98 - 24%	98 - 13%	99 - 37%	94 - 15%	99 - 37%	94 - 15%	98 - 24%	98 - 13%	99 - 5%	99 - 1%
AURORA	DSP 400	230/50Hz	400	L		99 - 5%	99 - 1%		99 - 1%	99 - 1%	98 - 1%	97 - 1%	96 - 0%	99 - 1%	96 - 0%	99 - 1%	98 - 1%	97 - 1%		
Berker	2861	230/50Hz	50-420	T					99 - 42%	99 - 27%	96 - 22%	97 - 21%	99 - 36%	94 - 28%	99 - 36%	94 - 28%	96 - 22%	97 - 21%	99 - 8%	99 - 2%
Bticino	L/N/NT4411N	230/50Hz	400	L			97 - 11%	97 - 11%	98 - 10%	97 - 3%	93 - 8%	88 - 3%	95 - 7%	94 - 3%	95 - 7%	94 - 3%	93 - 8%	88 - 3%	92 - 1%	90 - 9%
Bticino	L/N/NT4408	230/50Hz	600	L					98 - 1%	99 - 1%	97 - 1%	96 - 1%		95 - 1%		95 - 1%	97 - 1%	96 - 1%	97 - 1%	99 - 1%
Bticino	NT4402N	230/50Hz	500	R						99 - 61%										
Busch-Jaeger	6513 U-102	230/50Hz	40-420	T			99 - 21%	99 - 44%	99 - 27%	99 - 48%	99 - 21%	99 - 31%	98 - 15%	96 - 39%	94 - 21%	96 - 39%	94 - 21%	99 - 31%	98 - 15%	98 - 29%
Busch-Jaeger	6523 U-102	230/50Hz	100	L				98 - 18%	99 - 12%	99 - 12%	98 - 9%	99 - 9%	98 - 8%	99 - 11%	98 - 8%	99 - 11%	98 - 9%	99 - 9%	98 - 1%	96 - 1%
Busch-Jaeger	2250 U	230/50Hz	60-600	L					99 - 8%	99 - 12%	99 - 8%	95 - 12%	99 - 11%	94 - 13%	99 - 11%	94 - 13%	99 - 8%	95 - 12%	87 - 1%	99 - 1%
Busch-Jaeger	6526 U	230/50Hz	420	L																
Busch-Jaeger	2247 U-500	230/50Hz	60-500	L					99 - 23%	97 - 27%	81 - 21%	96 - 24%	99 - 25%	94 - 26%	99 - 25%	94 - 26%	81 - 21%	96 - 24%	83 - 1%	101 - 1%
CENTURY CONTROL	MULTI DIMMER	230/50Hz	60-600	L					99 - 10%	99 - 15%	98 - 9%	99 - 12%	99 - 7%	102 - 14%	99 - 7%	102 - 14%	98 - 9%	99 - 12%	99 - 1%	99 - 1%
DINUY	RE EL1 LE1	230/50Hz	400	L / T															99 - 1%	99 - 1%
ELKO	400GLI	230/50Hz	40-400	T			99 - 5%	98 - 1%	96 - 4%	99 - 1%	97 - 1%	97 - 1%	94 - 4%	98 - 1%	94 - 4%	98 - 1%	97 - 1%	97 - 1%	74 - 3%	91 - 9%
ELKO	315GLE	230/50Hz	20-315	T		99 - 2%	99 - 19%	99 - 17%	99 - 33%	66 - 24%	98 - 26%	99 - 21%	98 - 37%	98 - 26%	98 - 37%	98 - 26%	98 - 26%	99 - 21%	94 - 6%	90 - 1%
ELKO	600GLi	230/50Hz	40-600	L					95 - 30%	99 - 1%	97 - 1%	96 - 25%		92 - 1%		92 - 1%	97 - 1%	96 - 25%	99 - 1%	99 - 1%
ELKO	600GLE/I	230/50Hz	400	L / T					89 - 1%	92 - 1%	97 - 1%	97 - 1%		95 - 1%		95 - 1%	97 - 1%	97 - 1%	99 - 1%	97 - 1%
ELKO	420GLE/I	230/50Hz	40-420	U															99 - 1%	99 - 1%
ELKO	1000LRI	230/50Hz	1000	L					99 - 1%	99 - 1%	97 - 1%		97 - 0%	101 - 1%	97 - 0%	101 - 1%	97 - 1%			
ELKO	630GLE	230/50Hz	20-630	T					99 - 15%	99 - 8%	97 - 11%	98 - 7%	97 - 18%	94 - 8%	97 - 18%	94 - 8%	97 - 11%	98 - 7%	99 - 2%	99 - 1%
Eltako	EUD61NPN-UC	230/50Hz	5-400	R / L / C																
Feller	40600.RL	230/50Hz	40-600	L					95 - 30%	99 - 1%	97 - 1%	96 - 25%		92 - 1%		92 - 1%	97 - 1%	96 - 25%	99 - 1%	99 - 1%
Feller	40600.RC	230/50Hz	20-630	T					99 - 15%	99 - 8%	97 - 11%	98 - 7%	97 - 18%	94 - 8%	97 - 18%	94 - 8%	97 - 11%	98 - 7%	99 - 2%	99 - 1%
Feller	40200.LEDxxx	230/50Hz	525	T					99 - 24%	99 - 16%	98 - 21%	98 - 14%	96 - 25%	99 - 19%	96 - 25%	99 - 19%	98 - 21%	98 - 14%		
Feller	40600 RLC	230/50Hz	400	L / T					89 - 1%	92 - 1%	97 - 1%	97 - 1%		95 - 1%		95 - 1%	97 - 1%	97 - 1%	99 - 1%	97 - 1%
Feller	40420.RLC	230/50Hz	600	L															99 - 1%	99 - 1%
Feller	31000	230/50Hz	1000	L					99 - 1%	99 - 1%	97 - 1%		97 - 0%	101 - 1%	97 - 0%	101 - 1%	97 - 1%			
GIRA	226200	230/50Hz	20-500	L			99 - 11%	99 - 1%	99 - 34%	99 - 37%	98 - 29%	99 - 31%	99 - 32%	99 - 39%	99 - 32%	99 - 39%	98 - 29%	99 - 31%	82 - 1%	92 - 1%
Gira	030700	230/50Hz	20-525	T		99 - 16%	99 - 33%	99 - 28%	99 - 30%	99 - 19%	98 - 23%	97 - 14%	96 - 28%	99 - 19%	96 - 28%	99 - 19%	98 - 23%	97 - 14%	98 - 15%	92 - 4%
Gira	117600	230/50Hz	50-420	U					98 - 43%	99 - 29%	97 - 23%	97 - 21%	99 - 39%	95 - 30%	99 - 39%	95 - 30%	97 - 23%	97 - 21%	99 - 16%	56 - 9%
Gira	1224 LEDUDE	230/50Hz	LED						99 - 6%	99 - 8%	98 - 11%	98 - 5%	97 - 5%	99 - 8%	97 - 5%	99 - 8%	98 - 11%	98 - 5%	99 - 1%	98 - 1%
Gira	217400	230/50Hz	250	T															99 - 15%	99 - 16%

*MR16 and AR111 versions tested with HTM 70 transformer

DIMMER KOMPATIBILITÄT GlowDim

Legend					PARATHOM+ MR16 35 GLOWdim 36**		PARATHOM+ PAR16 50 GLOWdim 36°		PARATHOM+ CL A 40 GLOWdim		PARATHOM+ CL A 60 GLOWdim		PARATHOM+ CL B / BA GLOWdim		PARATHOM+ CL P GLOWdim		PARATHOM+ Globe GLOWdim		PARATHOM PRO AR111 GLOWdim*	
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)																			
	Limited dimmability with indicated number of lamps (dimming range smaller than 75%)				EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code		EAN / Basic Code	
	Undesired dimmability																			
	Not relevant																			
Not tested					4058075052802 / AC03896		4058075052826 / AC03897		4058075808539 / AC02140		4058075801417 / AC02143		4058075808157 / AC02154 4058075815056 / AC02155		4058075809062 / AC02228		4058075808959 / AC02157		4058075812857 / AC02488 4058075812932 / AC02489	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 5 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type																
Hager	WUD87	230/50Hz	400	LED-U																
Hamilton	KP1X40	230/50Hz	400	L					99 - 13%	99 - 15%	87 - 11%	93 - 14%	98 - 16%	95 - 16%	98 - 16%	95 - 16%	87 - 11%	93 - 14%	99 - 1%	88 - 1%
Hugo Müller	paladin 872110 led	230/50Hz	400	L / T															99 - 1%	99 - 1%
Jung	225 NVDE	230/50Hz	20-500	L			99 - 11%	99 - 1%	99 - 34%	99 - 37%	98 - 29%	99 - 31%	99 - 32%	99 - 39%	99 - 32%	99 - 39%	98 - 29%	99 - 31%	82 - 1%	92 - 1%
Jung	225 TDE	230/50Hz	20-525	T		99 - 16%	99 - 33%	99 - 28%	99 - 30%	99 - 19%	98 - 23%	97 - 14%	96 - 28%	99 - 19%	96 - 28%	99 - 19%	98 - 23%	97 - 14%	98 - 15%	92 - 4%
Jung	254 UDIE1	230/50Hz	50-420	U					98 - 43%	99 - 29%	97 - 23%	97 - 21%	99 - 39%	95 - 30%	99 - 39%	95 - 30%	97 - 23%	97 - 21%	99 - 16%	56 - 9%
Jung	1224 LEDUDE	230/50Hz		LED					99 - 6%	99 - 8%	98 - 11%	98 - 5%	97 - 5%	99 - 8%	97 - 5%	99 - 8%	98 - 11%	98 - 5%	99 - 1%	98 - 1%
Jung	3904 REGHE	230/50Hz	250	T															99 - 15%	99 - 16%
Legrand	665114	230/50Hz	400	L			97 - 11%	97 - 11%	98 - 10%	97 - 3%	93 - 8%	88 - 3%	95 - 7%	94 - 3%	95 - 7%	94 - 3%	93 - 8%	88 - 3%	92 - 1%	90 - 9%
Legrand	078407 / 079207	230/50Hz	400	L			97 - 11%	97 - 11%	98 - 10%	97 - 3%	93 - 8%	88 - 3%	95 - 7%	94 - 3%	95 - 7%	94 - 3%	93 - 8%	88 - 3%	92 - 1%	90 - 9%
Legrand	281080	230/50Hz	500	L																
Legrand	281084	230/50Hz	500	L																
Legrand	048871	230/50Hz	3-150	LED																
Legrand	617030	230/50Hz	600	L																
Legrand	770061	230/50Hz	400	RL					99 - 67%	98 - 41%		96 - 35%	98 - 69%	96 - 42%	98 - 69%	96 - 42%		96 - 35%	97 - 1%	99 - 1%
Legrand	099314	230/50Hz	300	L						99 - 1%	97 - 1%	98 - 1%	96 - 0%	95 - 1%	96 - 0%	95 - 1%	97 - 1%	98 - 1%		
Legrand	770062	230/50Hz	400	T					99 - 1%	95 - 1%	97 - 1%	97 - 1%	95 - 0%	90 - 1%	95 - 0%	90 - 1%	97 - 1%	97 - 1%	100 - 1%	94 - 1%
Legrand	617031	230/50Hz	1000	L															47 - 1%	86 - 1%
Legrand	078405	230/50Hz	600	L					98 - 1%	99 - 1%	97 - 1%	96 - 1%		95 - 1%		95 - 1%	97 - 1%	96 - 1%	97 - 1%	99 - 1%
MASTER	DM-DGL	230/50Hz	1000	L					99 - 53%	99 - 65%			98 - 49%		98 - 49%					
MASTER	DM-2500	230/50Hz	2500	L					99 - 1%	99 - 0%	99 - 1%	99 - 1%	98 - 0%	102 - 1%	98 - 0%	102 - 1%	99 - 1%	99 - 1%		
Merten	MEG5136-0000	230/50Hz	20-315	T		99 - 2%	99 - 19%	99 - 17%	99 - 33%	66 - 24%	98 - 26%	99 - 21%	98 - 37%	98 - 26%	98 - 37%	98 - 26%	98 - 26%	99 - 21%	94 - 6%	90 - 1%
Merten	MEG5133-0000	230/50Hz	40-600	L					95 - 30%	99 - 1%	97 - 1%	96 - 25%		92 - 1%		92 - 1%	97 - 1%	96 - 25%	99 - 1%	99 - 1%
Merten	MEG5137-0000	230/50Hz	20-630	T					99 - 15%	99 - 8%	97 - 11%	98 - 7%	97 - 18%	94 - 8%	97 - 18%	94 - 8%	97 - 11%	98 - 7%	99 - 2%	99 - 1%
Merten	MEG5134-0000	230/50Hz	525	T					99 - 24%	99 - 16%	98 - 21%	98 - 14%	96 - 25%	99 - 19%	96 - 25%	99 - 19%	98 - 21%	98 - 14%		
Merten	MEG5139-0000	230/50Hz	400	L / T					89 - 1%	92 - 1%	97 - 1%	97 - 1%		95 - 1%		95 - 1%	97 - 1%	97 - 1%	99 - 1%	97 - 1%
Merten	MEG5138-0000	230/50Hz	40-420	U															99 - 1%	99 - 1%
Merten	MEG 5170-0300	230/50Hz	10-200	T																
Merten	MEG 5131	230/50Hz	40-400	L					83 - 1%	99 - 1%	96 - 1%	97 - 1%		97 - 1%		97 - 1%	96 - 1%	97 - 1%	99 - 1%	99 - 1%
Merten	MEG 5132	230/50Hz	40-400	L					83 - 1%	99 - 1%	96 - 1%	97 - 1%		97 - 1%		97 - 1%	96 - 1%	97 - 1%	99 - 1%	99 - 1%
Merten	MEG 5140	230/50Hz	9-100	L					99 - 0%	99 - 1%	91 - 1%	94 - 1%	100 - 0%	95 - 1%	100 - 0%	95 - 1%	91 - 1%	94 - 1%	45 - 1%	94 - 1%
Merten	MEG 5135	230/50Hz	60-1000	L					99 - 1%	99 - 1%	97 - 1%		97 - 0%	101 - 1%	97 - 0%	101 - 1%	97 - 1%			
MK	K4501	230/50Hz	180	L					99 - 12%	99 - 15%	89 - 12%	95 - 12%	96 - 9%	102 - 14%	96 - 9%	102 - 14%	89 - 12%	95 - 12%	99 - 8%	85 - 5%

*MR16 and AR111 versions tested with HTM 70 transformer

DIMMER KOMPATIBILITÄT GlowDim

Legend					PARATHOM+ MR16 35 GLOWdim 36**		PARATHOM+ PAR16 50 GLOWdim 36°		PARATHOM+ CL A 40 GLOWdim		PARATHOM+ CL A 60 GLOWdim		PARATHOM+ CL B / BA GLOWdim		PARATHOM+ CL P GLOWdim		PARATHOM+ Globe GLOWdim		PARATHOM PRO AR111 GLOWdim*	
	Very good dimmability with indicated number of lamps (dimming range greater than 75%)																			
	Limited dimmability with indicated number of lamps (dimming range smaler than 75%)																			
	Undesired dimmability																			
	Not relevant																			
Not tested					4058075052802 / AC03896		4058075052826 / AC03897		4058075808539 / AC02140		4058075801417 / AC02143		4058075808157 / AC02154 4058075815056 / AC02155		4058075809062 / AC02228		4058075808959 / AC02157		4058075812857 / AC02488 4058075812932 / AC02489	
Dimmer					Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 5 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps	Dimming range 1 Lamp	Dimming range 4 Lamps
Brand	Model	Voltage range	Power	Type																
NEXUS	881P-01	230/50Hz	400	L																
NIKO	310-01900 / 01901	230/50Hz	200	L / T																
NIKO	330-00700 / 00701	230/50Hz	200	L / T																
Odace	S520511	230/50Hz	40-600	L																
Odace	S520512	230/50Hz	525	T																
Odace	S520515	230/50Hz	40-420	U																
Odace	S520518	230/50Hz	9-100	L																
Osram	HTI DALI 315 DIM	230/50Hz	20-315	DALI-T																
PEHA	435 HAN	230/50Hz	60-600	L																
Schneider	400GLI	230/50Hz	40-400	T																
Schneider	SBD315RC	230/50Hz	20-315	T																
Schneider	SBD600RL	230/50Hz	40-600	L																
Schneider	SBD630RC	230/50Hz	20-630	T																
Schneider	SBD200LED	230/50Hz	525	T																
Schneider	SBD600RCRL	230/50Hz	400	L / T																
Schneider	SBD420RCRL	230/50Hz	40-420	U																
Schneider	5170	230/50Hz	10-200	T																
Schneider	SBD400RL	230/50Hz	40-400	L																
Schneider	SBD5PL	230/50Hz	9-100	L																
Schneider	ATTD1000RL	230/50Hz	1000	L																
Shuttle	SDIM-T-LED-500W	230/50Hz	2-500	T & LED-T																
Siemens	5TC8 284	230/50Hz	20-525	T																
Siemens	5WG1-528-1AB31	230/50Hz	500	T																
VADSBO	LD 220	230/50Hz	1-200	U																
VARILIGHT	HQ3W	230/50Hz	400	L																
VARILIGHT	JQP401W	230/50Hz	400	T																
Vimar	20135	230/50Hz	100	L / T																
ZANO	WH401	230/50Hz	400	L																
ZANO	WH251	230/50Hz	250	L																
ZANO	Z GRID 700	230/50Hz	250	LED																
ZANO	Z GRID 500	230/50Hz	500	L																

*MR16 and AR111 versions tested with HTM 70 transformer

Please Note:

- The compatibility list is based upon testing conducted by the manufacturer in a lab simulated environment, and the results can vary in certain field applications due to a number of factors. OSRAM does not take over any responsibility, warranty or liability that this results can also achieved by using the devices under other conditions, or when using successor models of the tested devices, or different models of the same manufacturer, or when using other LED lamp types
- The absence of a dimmer from this chart does not necessarily imply incompatibility.
- Please reference the dimmer manufacturer's instructions for installation.
- LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance).
- Subject to change without notice
- Errors and omission excepted
- Always make sure to use the most recent release

Application Notes:

- For best dimming results trailing edge dimmer type is recommended.
- Trailing edge type dimmer requires the neutral wire for installation.

Bitte beachten:

- Die Kompatibilitätsliste basiert auf Tests, die der Hersteller in einer im Labor simulierten Umgebung durchgeführt hat. Die Ergebnisse können aufgrund verschiedener Faktoren in manchen Praxisanwendungen abweichen. OSRAM übernimmt keinerlei Verantwortung, Garantie oder Haftung dafür, dass diese Ergebnisse tatsächlich mit den Geräten unter anderen Bedingungen, mit Nachfolgemodellen der getesteten Geräte, mit anderen Modellen desselben Herstellers oder bei Verwendung anderer LED-Lampentypen erreicht werden.
- Das Fehlen eines Dimmers in der Abbildung bedeutet nicht, dass ein Dimmer nicht kompatibel ist.
- Lesen Sie stets die Installationsanweisungen des Dimmerherstellers.
- LED-Lampen bestehen aus mehreren elektronischen Komponenten. Unter ungünstigen Bedingungen können diese Störgeräusche erzeugen. Im Resonanzfall können selbst geringe Geräusche einen hörbaren Effekt hervorrufen. Einflussfaktoren können die Installation, die Gestaltung des Lampenträgers, die Leuchte (akustischer Resonanzeffekt), der Dimmer oder der Trafo (Oberschwingungen oder elektronische Resonanz) sein.
- Änderungen vorbehalten.
- Irrtümer und Auslassungen vorbehalten.
- Vergewissern Sie sich, dass Sie stets die aktuellste Version benutzen.

Anwendungshinweis:

- Um bestmögliche Dimmergebnisse zu erzielen, wird die Verwendung von Phasenabschnitt-Dimmern empfohlen.
- Phasenabschnitt-Dimmer erfordern bei der Installation einen Neutralleiter.

LEDVANCE GmbH

Head Office:

Parkring 29-33
85748 Garching, Germany
Phone +49 89 780673-100
Fax +49 89 780673-XXX
www.ledvance.com