

Spike lights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled



GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Long spike included for extra stability
Robust cable for outdoor use
Small & discreet
Single point source LED
IP65 allows for use in exterior spaces

Beam angle: 26°



SL030

1W LED spike light

FEATURES

Wattage	1W(350mA) 2W(700mA)
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	90°
Input	Driver required (350mA / 700mA)
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	1
Inrush Current	N/A
Construction material	Stainless steel (316)
Weight	700g
Maximum ambient temperature	35°C
SELV	N/A
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Finish	Colour	Beam angle	CRI	350mA			700mA		
					lm	lm/W	lx at 1m	lm	lm/W	lx at 1m
SL030 F NW	Stainless steel 316	4000K	26°	>80Ra	95	95	267	140	70	393
SL030 F WW	Stainless steel 316	3000K	26°	>80Ra	75	75	210	135	68	379
SL030 F 27	Stainless steel 316	2700K	26°	>80Ra	70	70	196	120	60	337
SL030 F AMBER	Stainless steel 316	Amber	26°	-	-	-	-	-	-	-
SL030 F BLUE	Stainless steel 316	Blue	26°	-	-	-	-	-	-	-
SL030 F GREEN	Stainless steel 316	Green	26°	-	-	-	-	-	-	-
SL030 F RED	Stainless steel 316	Red	26°	-	-	-	-	-	-	-

WIRING INFORMATION

Cable / flying lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220V-240V	Yes	No	1	1	9
PLR/350 1-5	220V-240V	Yes	No	1	1	5
PLD UNI-DRIVE 700MA	220V-240V	Yes	Yes (1-10V)	2	1	10

ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold separately	422-423
WCR 275 BLACK	2-core rubber cable	Sold separately	423
PDC/GRID DIMMER	1-10V dimmer module	Sold separately	422