



COLLINGWOOD
LIGHTING



FEATURES & BENEFITS

- › Equivalent to 50W halogen
- › MR16 for retrofit into existing housings
- › 3-year extended warranty available

DM02

MR16 high output single source LED replacement



Suitable for use indoors



3-year extended warranty available



HOUSING DEPENDANT

35DCM

PHOTOMETRICS @ 25°C

Adding a housing to this module will affect photometric readings

Colour	Beam angle	Product code	CRI	lm	lm/W	lx at 1m
3000K	24°	DM022430	>80Ra	580	92	1997

DRIVER REQUIRED FOR DM02 RANGE

Product code	Input power	Description
PSDIM180	8.5W	Mains dimmable, IP20, 180mA driver

GENERAL

Building regulations	Product is not fire-rated
Construction material	Aluminium

WIRING

Cable / flying lead	Plug & Play into driver
Type of wiring required	Plug & Play

NB: Removal of plugs will render this product non-returnable

LED DRIVERS

Bathroom zone applicable to fitting only

Product code	mA	SELV	Dimming	Bathroom zone	Min	Max
PSDIM180	180	Yes	Yes (mains)	-	1	1

ACCESSORIES

Product code	Description
DH02WH	Adjustable MR16 pinhole housing for the DM01 & DM02
DH03WH	Adjustable MR16 baffled housing for the DM01 & DM02
DH04WH	Adjustable MR16 highlight housing for the DM01 & DM02
DH05WH	Adjustable MR16 wall wash housing for the DM01 & DM02
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types
DM298GRID	LED mains grid dimmer
DM298FP	Faceplate dimmer

