



## GL018 C AB

Small antique brass LED marker light

### FEATURES

Wattage	0.5W
IP rating	IP68
IK rating	IK07
Colour flexibility	Fixed colour
Walk over / drive over	Walk over (5mm toughened glass)
Input	24V DC
LED lifetime	30,000h
SDCM	3SDCM

### INSTALLATION INFORMATION

Cut out size	Ø 28mm
Bathroom zone	0
Inrush current	N/A
Construction material	Brass
Weight	300g
Maximum ambient temperature	35°C
SELV	N/A
Electric class [1, 2, 3]	3

### PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
GL018 C AB NW	4000K	120°	>70Ra	3	6	1
GL018 C AB WW	3000K	120°	>80Ra	3	6	1
GL018 C AB 27	2700K	120°	>80Ra	3	6	1
GL018 C AB AMBER	Amber	120°	-	-	-	-
GL018 C AB BLUE	Blue	120°	-	-	-	-
GL018 C AB GREEN	Green	120°	-	-	-	-
GL018 C AB RED	Red	120°	-	-	-	-

### WIRING INFORMATION

Cable / flying lead	1m (H05RN-F) rubberised cable (outside diameter: 6mm)
Type of wiring required	Parallel

### LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PS1524	220-240V	Yes	Yes (PDCINT1-10V)	0 (1 when dimming)	1	30
PS5024	N/A	Yes	Yes (PDCINT1-10V)	0 (1 when dimming)	1	100
PSDIP10024	N/A	Yes	Yes (1-10V)	0 (1 when dimming)	1	200

### ACCESSORIES

JB1 / JB5 / JB6	IP68 waterproof connectors	Sold separately	422-423
PDC/GRID DIMMER	Grid dimmer kit for multiple fitting types	Sold separately	422
PDCINT1-10V	1-10V dimming interface for use with 24V LED drivers	Sold separately	412

## Ground lights.

01604 495 151  
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

### GUARANTEE / WARRANTY

7 year extended warranty

### FEATURES & BENEFITS

- Frosted effect for softer tone of light
- Robust cable for outdoor use
- Shallow depth for easy installation
- Solid brass for antique effect
- Parallel wiring for easier installation and more fittings to a power supply

Beam angle: 120°

