

Spike lights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

High efficacy - up to 144lm/W

Improved look and feel with single LED



New stainless steel and anodised bronze finishes

Higher light output than predecessor

Low voltage can now run on 700mA drivers

Reduced body length by 12% for a neat and compact appearance

Beam angle: 40°



SL220

Low voltage LED spike light

FEATURES

Wattage	2.2W (350mA) 4.6W (700mA)
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	90°
Input	Driver required (350mA / 700mA)
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	1
Inrush Current	N/A
Construction material	Anodised aluminium Stainless steel 316 Copper
Weight	SL220B / SL220Z: 512g SL220Z: 1301g SL220D: 1000g
Maximum ambient temperature	50°C
SELV	Driver Dependant
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Finish	Colour	Beam angle	CRI	350mA			700mA		
					lm	lm/W	lx at 1m	lm	lm/W	lx at 1m
SL220BWBX40	Black	4000K	40°	>80Ra	310	141	705	530	115	1205
SL220BWBX30	Black	3000K	40°	>80Ra	300	136	682	520	113	1182
SL220BWBX27	Black	2700K	40°	>80Ra	290	132	659	515	112	1171
SL220ZWBX40	Bronze	4000K	40°	>80Ra	310	141	705	530	115	1205
SL220ZWBX30	Bronze	3000K	40°	>80Ra	300	136	682	520	113	1182
SL220ZWBX27	Bronze	2700K	40°	>80Ra	290	132	659	515	112	1171
SL220DWBX30	Stainless steel 316	3000K	40°	>80Ra	300	136	682	520	113	1182
SL220DWBX40	Stainless steel 316	4000K	40°	>80Ra	310	141	705	530	115	1205
SL220DWBX27	Stainless steel 316	2700K	40°	>80Ra	290	132	659	515	112	1171
SL220CWBX27	Copper	2700K	40°	>80Ra	290	132	659	515	112	1171

WIRING INFORMATION

Cable / flying lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220V-240V	Yes	No	1	1	4
PLR/350 1-5	220V-240V	Yes	No	1	1	3
PLD UNI-DRIVE 700MA	220V-240V	Yes	Yes (1-10V)	2	1	5

ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold separately	422-423
PDC/GRID DIMMER	1-10V dimmer module	Sold separately	422
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold separately	282
GS220	Stylish, baffle-style snoot, perfect for creating a moonlighting effect	Sold separately	282