

Spike lights.

01604 495 151
collingwoodlighting.com

-  @collingwoodLED
-  /collingwoodlighting
-  collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Adjustable pole-mounted twin heads are perfect for illuminating paths, steps and trees




Easily ground mounted with spiked pole and single cable for quick installation

Elegant and discreet black and bronze finishes

Available in both low voltage and mains voltage

Highly efficient: up to 114lm/W

Beam angle: 40°



SL230

Low voltage LED twin pole spike light

FEATURES

Wattage	4.4W (350mA) 9.2W (700mA)
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	90°
Rotatable	330°
Input	Driver required (350mA / 700mA)
LED lifetime	70,000h L70 B10
SDCM	3SDCM

INSTALLATION INFORMATION

Bathroom zone	2
Inrush Current	N/A
Construction material	Anodised aluminium
Weight	1401g
Maximum ambient temperature	35°C
SELV	N/A
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Finish	Colour	Beam angle	CRI	350mA			700mA		
					lm	lm/W	lx at 1m	lm	lm/W	lx at 1m
SL230BWBX40	Black	4000K	40°	>80Ra	620	144	2X 705	1060	114	2X 1205
SL230BWBX30	Black	3000K	40°	>80Ra	600	140	2X 682	1040	112	2X 1182
SL230BWBX27	Black	2700K	40°	>80Ra	580	135	2X 659	1030	111	2X 1171
SL230ZWBX40	Bronze	4000K	40°	>80Ra	620	144	2X 705	1060	114	2X 1205
SL230ZWBX30	Bronze	3000K	40°	>80Ra	600	140	2X 682	1040	112	2X 1182
SL230ZWBX27	Bronze	2700K	40°	>80Ra	580	135	2X 659	1030	111	2X 1171

WIRING INFORMATION

Cable / flying lead	3m H05RN-F rubberised cable (outside diameter: 6mm)
Type of wiring required	Series

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PLU/350 1-9	220V-240V	Yes	No	1	1	2
PLD UNI-DRIVE 700MA	220V-240V	Yes	Yes (1-10V)	1	1	3

ACCESSORIES

JB2 / JB4 / JB6	Waterproof junction box / Gel filled waterproof connectors	Sold separately	422-423
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold separately	282
GS220	Simple snoot to reduce glare whilst maintaining a good light distribution	Sold separately	282