



# SL230

Mains voltage LED twin pole spike light

## FEATURES

Wattage	11.4W
IP rating	IP65
Colour flexibility	Fixed colour
Tilttable	90°
Rotatable	330°
Input	Mains AC
LED lifetime	70,000h L70 B10
SDCM	3SDCM

## INSTALLATION INFORMATION

Bathroom zone	2
Inrush Current	120A 37µs
Construction material	Anodised aluminium
Weight	1577g
Maximum ambient temperature	35°C
SELV	Yes
Electric class (1, 2, 3)	2

## PHOTOMETRICS @ 25°C

Product code	Finish	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
SL230BWB40	Black	4000K	40°	>80Ra	1060	93	2X 1205
SL230BWB30	Black	3000K	40°	>80Ra	1040	91	2X 1182
SL230BWB27	Black	2700K	40°	>80Ra	1030	90	2X 1171
SL230ZWB27	Bronze	2700K	40°	>80Ra	1030	90	2X 1171
SL230ZWB30	Bronze	3000K	40°	>80Ra	1040	91	2X 1182
SL230ZWB40	Bronze	4000K	40°	>80Ra	1060	93	2X 1205

## WIRING INFORMATION

Cable / flying lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of wiring required	Parallel

## LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220V-240V	Yes	No	2	-	-

## ACCESSORIES

JB5	Gel filled waterproof connector	Sold separately	423
GH220	Simple hood to reduce glare whilst maintaining a good light distribution	Sold separately	282
GS220	Simple snoot to reduce glare whilst maintaining a good light distribution	Sold separately	282

# Spike lights.

01604 495 151  
collingwoodlighting.com

- @collingwoodLED
- /collingwoodlighting
- collingwoodled

## GUARANTEE / WARRANTY

7 year extended warranty

## FEATURES & BENEFITS

Adjustable pole-mounted twin heads are perfect for illuminating paths, steps and trees

Easily ground mounted with spiked pole and single cable for quick installation

Elegant and discreet black and bronze finishes

Available in both low voltage and mains voltage

Highly efficient: up to 93lm/W

Beam angle: 40°

