

Ground lights.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled



GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Straight to mains
Large diameter
Drive over up to 18kN (approx. a 7 ton vehicle) - use with TUBE/68
Marine grade stainless steel 316
Long lifetime of 70,000hrs

Beam angle: 90°



GL200 (1 window - 2 windows)

Large domed marker light

FEATURES

Wattage	5.7W
IP rating	IP67
IK rating	IK10
Colour flexibility	Fixed colour
Walk over / drive over	Drive over (15mph maximum)
Input	Mains AC
LED lifetime	70,000h L70
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 65mm
Bathroom zone	2
Inrush current	31A 0.12ms
Construction material	Stainless steel (316)
Weight	960g
Maximum ambient temperature	35°C
SELV	Yes
Electric class (1, 2, 3)	1

PHOTOMETRICS @ 25°C

Product code	Window style	Colour	Beam angle	CRI	lm	lm/W
GL200DX1X40	1 window	4000K	90°	>80Ra	10	2
GL200DX1X30	1 window	3000K	90°	>80Ra	10	2
GL200DX1X27	1 window	2700K	90°	>80Ra	10	2
GL200DX2140	2 windows, 1 direction	4000K	90°	>80Ra	20	4
GL200DX2130	2 windows, 1 direction	3000K	90°	>80Ra	20	4
GL200DX2127	2 windows, 1 direction	2700K	90°	>80Ra	20	4
GL200DX2240	2 windows, 2 directions	4000K	90°	>80Ra	20	4
GL200DX2230	2 windows, 2 directions	3000K	90°	>80Ra	20	4
GL200DX2227	2 windows, 2 directions	2700K	90°	>80Ra	20	4

WIRING INFORMATION

Cable / flying lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of wiring required	Parallel

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	-	-

ACCESSORIES

TUBE/68	Installation tube	Sold separately	236
JB5	Gel filled waterproof connector	Sold separately	423
WC 5-9	Quick waterproof connector	Sold separately	422