



GL200 (3 windows - 4 windows)

Large domed marker light

FEATURES

Wattage	5.7W
IP rating	IP67
IK rating	IK10
Colour flexibility	Fixed colour
Walk over / drive over	Drive over (15mph maximum)
Input	Mains AC
LED lifetime	70,000h L70
SDCM	3SDCM

INSTALLATION INFORMATION

Cut out size	Ø 65mm
Bathroom zone	2
Inrush current	31A 0.12ms
Construction material	Stainless steel (316)
Weight	960g
Maximum ambient temperature	35°C
SELV	Yes
Electric class [1, 2, 3]	1

PHOTOMETRICS @ 25°C

Product code	Window style	Colour	Beam angle	CRI	lm	lm/W
GL200DX3X40	3 windows	4000K	90°	>80Ra	30	5
GL200DX3X30	3 windows	3000K	90°	>80Ra	30	5
GL200DX3X27	3 windows	2700K	90°	>80Ra	30	5
GL200DX4X40	4 windows	4000K	90°	>80Ra	40	7
GL200DX4X30	4 windows	3000K	90°	>80Ra	40	7
GL200DX4X27	4 windows	2700K	90°	>80Ra	40	7

WIRING INFORMATION

Cable / flying lead	3m H05RN-F rubberised cable (outside diameter: 7mm)
Type of wiring required	Parallel

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	No	2	-	-

ACCESSORIES

TUBE/68	Installation tube	Sold separately	236
JB5	Gel filled waterproof connector	Sold separately	423
WC 5-9	Quick waterproof connector	Sold separately	422

Ground lights.

01604 495 151
collingwoodlighting.com

@collingwoodLED

/collingwoodlighting

collingwoodled

GUARANTEE / WARRANTY

7 year extended warranty

FEATURES & BENEFITS

Straight to mains

Large diameter

Drive over up to 18kN (approx. a 7 ton vehicle) - use with TUBE/68

Marine grade stainless steel 316

Long lifetime of 70,000hrs

Beam angle: 90°

