

Colour change.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

Low profile for easy installation
Installation tube available
Full RGBW colour range
Compatible with a large range of controllers
Marine grade stainless steel for use in outdoor and indoor environments



GL040CARGB

Colour change LED ground light (3.5W max.)

FEATURES

Wattage	3.5W
Wattage (Red)	1W
Wattage (Green)	1.2W
Wattage (Blue)	1.2W
IP rating	IP68
IK rating	IK08
Colour flexibility	RGB
Walk over / drive over	Walk over (5mm toughened glass)
Input	350mA
LED lifetime	50,000h L50 B50

INSTALLATION INFORMATION

Cut out size	Ø 65mm
Bathroom zone	1
Construction material	Stainless steel (316)
Weight	800g
Maximum ambient temperature	35°C
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
GL040CARGB	Red	18°	-	34	34	287
	Green	18°	-	68	56	697
	Blue	18°	-	8	7	8

WIRING INFORMATION

Cable / flying lead	2x 1m LED RGB 0.75mm ₂ cable (outside diameter: 6mm)
Type of wiring required	Series
PR3011	350mA power repeater, 4 RGBW channels, 350mA (for 1-6 product) (not included)
C100924	RGB & RGBW controller, 24V (not included)

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PS1524	220-240V	Yes	Yes	-	1	1
PS3024B	220-240V	Yes	Yes	-	1	2
PS7524	220-240V	Yes	Yes	-	1	5

ACCESSORIES

TUBE/68	Installation tube	Sold separately	236
JB7	5-pole IP68 inline connector	Sold separately	423
LED RGB 0.75 CABLE	4-core PVC cable	Sold separately	383
RC2819 / WC2820(BLK/WH) / TR2818	4/6/8 zone RF control for RGB & RGBW system	Sold separately	376 - 377
GLA01	Ground Light Accessory, square plate, stainless steel 316,	Sold separately	237

