




Colour change.

01604 495 151
collingwoodlighting.com

 @collingwoodLED
 /collingwoodlighting
 collingwoodled

GUARANTEE / WARRANTY

5 year extended warranty

FEATURES & BENEFITS

Complete with wall fixings for easy installation

Can rotate and be angled to direct light



Separate white LED for permanent use

Full RGBW colour range

Compatible with a large range of controllers

Marine grade stainless steel for use in outdoor and indoor environments

Beam angle: 45°



UL030RGBW

Colour change LED light (12W max.)

FEATURES

Wattage (White)	3W
Wattage (Red)	2W
Wattage (Green)	3W
Wattage (Blue)	3W
IP rating	IP68
Colour flexibility	RGBW
Tilttable	360°
Rotatable	360°
Input	350mA
LED lifetime	50,000h L50 B50

INSTALLATION INFORMATION

Bathroom zone	1
Construction material	Stainless steel (316)
Weight	900g
Maximum ambient temperature	35°C
Electric class (1, 2, 3)	3

PHOTOMETRICS @ 25°C

Product code	Colour	Beam angle	CRI	lm	lm/W	lx at 1m
UL030RGBW	White	45°	>80Ra	177	59	154
	Red	45°	>80Ra	106	53	60
	Green	45°	>80Ra	185	62	168
	Blue	45°	>80Ra	43	14	1

WIRING INFORMATION

Cable / flying lead	2x 1m CR575RGBW (outside diameter: 7.4mm)
Type of wiring required	Series
PR3011	350mA power repeater, 4 RGBW channels, 350mA (for 1-6 product) (not included)
C100924	RGB & RGBW controller, 24V (not included)

LED DRIVERS

Product code	Input	SELV	Dimming	Bathroom zone	Min	Max
PS1524	220-240V	Yes	Yes	-	1	1
PS3024B	220-240V	Yes	Yes	-	1	2
PS7524	220-240V	Yes	Yes	-	1	5

ACCESSORIES

JB7	5-pole IP68 inline connector	Sold separately	423
CR575RGBW	5-core PVC cable	Sold separately	382
RC2819 / WC2820(BLK/WH) / TR2818	4/6/8 zone RF control for RGB & RGBW system	Sold separately	376 - 377