

MG-CPM-04



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	130 °C
Self-extinguishing fire class according to UL 94	V0
Number of lines	4

WEIGHT AND DIMENSIONS

Length	10 mm
Base of the printable area	10 mm

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling for terminal block [EC000761]
--------------	---

MATERIAL COMPOSITION AND TREATMENTS

Silicone-free	Yes
Halogen free	Yes

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39269097

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4
Plates	MG2-QTB

MG-CPM-04

tipo	Colour	Sheet elements	Number of columns	Material	Width [mm]	Height of the printable area [mm]	Horizontal pitch between the sheet elements [mm]	Gross weight [g]	Software code
41391	White	48	12	Polycarbonate PC10200WH; PC10300WH	6	6	6	0,243	45
41390N	White	48	12	Polycarbonate PC10200WH; PC10300WH	5	5	5.2	0,283	42
41392	White	80	20	Polycarbonate PC10200WH; PC10300WH	3	3	3.5	0,160	43
41395	White	48	12	Polycarbonate PC10200WH; PC10300WH	5	5	5.2	0,266	31
41396	White	32	8	Polycarbonate PC10200WH; PC10300WH	8	8	8	0,456	48
41340N	Yellow	48	12	Polycarbonate PC10400YE	5	5	5.2	0,283	42
41346	Yellow	32	8	Polycarbonate PC10400YE	8	8	8	0,443	48

