

MG-SPM



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	130 °C
Self-extinguishing fire class according to UL 94	V0
Number of columns	4

WEIGHT AND DIMENSIONS

Horizontal pitch between the sheet elements	29 mm
---	-------

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39269097

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4

MG-SPM-02

tipo	Colour	Sheet elements	Number of lines	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code	Plates
43291	White	12	3	7	20	20	7	0,626	142	MG2-PSP

MG-SPM-03

tipo	Colour	Sheet elements	Number of lines	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code	Plates
32291	White	12	3	9	19	19	9	1,100	143	MG2-QTB

MG-SPM-07

tipo	Colour	Sheet elements	Number of lines	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code	Plates
32690	White	20	5	3.3	12	12	3.3	0,523	145	MG2-BSP

MG-SPM-09

tipo	Colour	Sheet elements	Number of lines	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code	Plates
32895	White	12	3	8	20	20	8	0,828	144	MG2-WTB

MG-SPM-11

tipo	Sheet elements	Number of lines	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Plates
32995	24	6	7	12	12	7	0,427	MG2-WSP