

MG-CPM-13

TERMINAL MARKER TAGS Entrelec SNK ZS



Features

TECHNICAL INFORMATION

|                                                  |        |
|--------------------------------------------------|--------|
| Minimum operating temperature                    | -40 °C |
| Maximum operating temperature                    | 130 °C |
| Self-extinguishing fire class according to UL 94 | V0     |
| Number of lines                                  | 4      |

WEIGHT AND DIMENSIONS

|                            |       |
|----------------------------|-------|
| Length                     | 12 mm |
| Base of the printable area | 12 mm |

CLASSIFICATION AND DATA ORDERING

|              |                                         |
|--------------|-----------------------------------------|
| ETIM Class 7 | Labelling for terminal block [EC000761] |
|--------------|-----------------------------------------|

MATERIAL COMPOSITION AND TREATMENTS

|               |     |
|---------------|-----|
| Silicone-free | Yes |
| Halogen free  | Yes |

LOGISTIC

|                              |            |
|------------------------------|------------|
| Storage temperature          | 10 ÷ 25 °C |
| Relative humidity of storage | 45 ÷ 55    |
| Customs code                 | 39269097   |

COMPATIBILITY

|                |          |
|----------------|----------|
| Ribbon         | MG2-ETR  |
| Printable with | MG3; MG4 |
| Plates         | MG2-ETB  |

MG-CPM-13

| tipo  | Colour | Sheet elements | Number of columns | Material                              | Width [mm] | Height of the printable area [mm] | Horizontal pitch between the sheet elements [mm] | Gross weight [g] | Software code |
|-------|--------|----------------|-------------------|---------------------------------------|------------|-----------------------------------|--------------------------------------------------|------------------|---------------|
| 41790 | White  | 56             | 14                | Polycarbonate<br>PC10200WH; PC10300WH | 5          | 5                                 | 5.2                                              | 0,240            | 113           |
| 41791 | White  | 48             | 12                | Polycarbonate<br>PC10200WH; PC10300WH | 6          | 6                                 | 6                                                | 0,317            | 114           |
| 41740 | Yellow | 56             | 14                | Polycarbonate PC10400YE               | 5          | 5                                 | 5.2                                              | 0,240            | 113           |
| 41741 | Yellow | 48             | 12                | Polycarbonate PC10400YE               | 6          | 6                                 | 6                                                | 0,270            | 114           |