

PTP

PUSH BUTTON LEGEND BASES



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	115 °C
Minimum application temperature	-40 °C
Maximum application temperature	115 °C
Colour	Black RAL 9005
Type of application surface	flat smooth
Self-extinguishing fire class according to UL 94	V0

WEIGHT AND DIMENSIONS

Width	30 mm
Length	48 mm

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Mounting for labelling material [EC002248]
--------------	--

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	No
Halogen free	No

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39269097

PTPO-22

tipo	Gross weight [g]
34802	2,760

PTPOA-22

tipo	Type of adhesive	Gross weight [g]
34902	acrylic double sided tape	2,860

PTPR-22

tipo	Gross weight [g]
34102	2,620

PTPRA-22

tipo	Type of adhesive	Gross weight [g]
34702	acrylic double sided tape	2,760

PTPS-22

tipo	Gross weight [g]
34002	2,860

PTPS-24

tipo	Gross weight [g]
68002	2,440

PTPSA-22

tipo	Type of adhesive	Gross weight [g]
34602	acrylic double sided tape	2,940

PTPSA-24

tipo	Type of adhesive	Gross weight [g]
68602	acrylic double sided tape	2,560