

MG-TAPW

TAGES FOR CABLES AND COMPONENTS, PRE-CUT, RIGID PVC



CERTIFICATIONS & APPROVALS

UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-30 °C
Maximum operating temperature	60 °C
Self-extinguishing fire class according to UL 94	V0

MATERIAL COMPOSITION AND TREATMENTS

Silicone-free

Yes

WEIGHT AND DIMENSIONS

Width

9 mm

LOGISTIC

Customs code

39204910

CLASSIFICATION AND DATA ORDERING

ETIM Class 7

Labelling material [EC001288]

MG-TAPW

tipo	Colour	Sheet elements	Number of lines	Number of columns	Material	Halogen free	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Storage temperature [°C]	Relative humidity of storage	Software code	Ribbon	Printable with	Plates
49090N	White	55	5	11	Rigid PVC10050WH	No	20	9	20	0,225	10 ÷ 25	45 ÷ 55	362	MG2-ETR	MG3; MG4	MG2-PLT
49040N	Yellow	55	5	11	Rigid PVC10050YE	No	20	9	20	0,222	10 ÷ 25	45 ÷ 55	362	MG2-ETR	MG3; MG4	MG2-PLT
49042N	Yellow	88	8	11	Rigid PVC10050YE	No	12	9	12	0,142	10 ÷ 25	45 ÷ 55	360	MG2-ETR	MG3; MG4	MG2-PLT
49043N	Yellow	77	7	11	Rigid PVC10050YE	No	15	9	15	0,163	10 ÷ 25	45 ÷ 55	361	MG2-ETR	MG3; MG4	MG2-PLT
49044	Yellow	20	2	10	Rigid PVC10050YE	No	50	9	50	0,615	10 ÷ 25	45 ÷ 55	376	MG2-ETR	MG3; MG4	MG2-PLT
49045N	Yellow	11	1	11	Rigid PVC10050YE	No	70	9	70	1,025	10 ÷ 25	45 ÷ 55	378	MG2-ETR	MG3; MG4	MG2-PLT
49091N	White	33	3	11	Rigid PVC10050WH	No	35	9	35	0,368	10 ÷ 25	45 ÷ 55	364	MG2-ETR	MG3; MG4	MG2-PLT
49093N	White	77	7	11	Rigid PVC10050WH	No	15	9	15	0,165	10 ÷ 25	45 ÷ 55	361	MG2-ETR	MG3; MG4	MG2-PLT
49094	White	20	2	10	Rigid PVC10050WH	No	50	9	50	0,613	10 ÷ 25	45 ÷ 55	376	MG2-ETR	MG3; MG4	MG2-PLT
49092N	White	88	8	11	Rigid PVC10050WH	No	12	9	12	0,145	10 ÷ 25	45 ÷ 55	360	MG2-ETR	MG3; MG4	MG2-PLT
49041N	Yellow	33	3	11	Rigid PVC10050YE	No	35	9	35	0,367	10 ÷ 25	45 ÷ 55	364	MG2-ETR	MG3; MG4	MG2-PLT
49095N	White	11	1	11	Rigid PVC10050WH	No	70	9	70	1,156	10 ÷ 25	45 ÷ 55	378	MG2-ETR	MG3; MG4	MG2-PLT
49046	Yellow	30	3	10	Rigid PVC10050YE	No	29	9	30	0,422	10 ÷ 25	45 ÷ 55	363	MG2-ETR	MG3; MG4	MG2-PLT
49066	Blue	30	3	10	Rigid PVC	No	29	9	30	0,407	10 ÷ 25	45 ÷ 55	363	MG2-ETR	MG3; MG4	MG2-PLT
49053N	Green	77	7	11	Rigid PVC	No	15	9	15		10 ÷ 25	45 ÷ 55	361	MG2-ETR	MG3; MG4	MG2-PLT
49055N	Green	11			Rigid PVC		70						378			
49096	White	30	3	10	Rigid PVC10050WH	No	29	9	30	0,420	10 ÷ 25	45 ÷ 55	363	MG2-ETR	MG3; MG4	MG2-PLT