

MG-DOG-HF

TAGS, PRE-CUT, IN POLYCARBONATE, HALOGEN FREE



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	130 °C
Self-extinguishing fire class according to UL 94	V0

MATERIAL COMPOSITION AND TREATMENTS

Silicone-free	Yes
Halogen free	Yes

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39206100

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4
Plates	MG2-PLT

MG-DOG-HF

tipo	Colour	Sheet elements	Number of lines	Number of columns	Material	Width [mm]	Hole diameter [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
48204-HF	White	8	2	4	Polycarbonate PC10050WH	25	5	50	50	50	1,410	868
48300-HF	White	6	3	2	Polycarbonate PC10050WH	35	4	35	35	35	2,080	870
48340-HF	Yellow	6	3	2	Polycarbonate PC10050YE	35	4	35	35	35	1,853	870
48392-HF	White	12	4	3	Polycarbonate PC10050WH	20	6.5	20	20	20	0,960	875
48397-HF	White	2	1	2	Polycarbonate PC10050WH	52	6.5	107	52	107	5,360	876
48352-HF	Green	12	4	3	Polycarbonate	20	6.5	20	20	20	0,933	875

