

MG-PTS

TAGS FOR BUTTONS, PRE-CUT, RIGID PVC



CERTIFICATIONS & APPROVALS

UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-30 °C
Maximum operating temperature	60 °C
Self-extinguishing fire class according to UL 94	V0
Number of lines	2

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4
Plates	MG2-PLT

MATERIAL COMPOSITION AND TREATMENTS

Silicone-free	Yes
Halogen free	No

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

tipo	Minimum application temperature [°c]	Maximum application temperature [°c]	Colour	Type of adhesive	Sheet elements	Number of columns	Material	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Customs code	Software code
15140	-30	60	Yellow	Acrylic double sided tape	6	3	Rigid PVC10050YE	30	40	30	40	2,632	39199080	1000
15141	-30	60	Yellow	Acrylic double sided tape	6	3	Rigid PVC10050YE	30	50	30	50	2,413	39199080	1001
15190	-30	60	White	Acrylic double sided tape	6	3	Rigid PVC10050WH	30	40	30	40	2,655	39199080	1000
15191	-30	60	White	Acrylic double sided tape	6	3	Rigid PVC10050WH	30	50	30	50	2,520	39199080	1001
15120	-30	60	Rosso	Acrylic double sided tape	6	3	Rigid PVC	30	40	30	40	2,667	39199080	1000
15100	-30	60	Black RAL 9005	Acrylic double sided tape	6	3	Rigid PVC	30	40	30	40	2,760	39199080	1000
15101	-30	60	Black RAL 9005	Acrylic double sided tape	6	3	Rigid PVC	50	30	30	50	2,627	39199080	1001
15180GY	-30	60	Grey	Acrylic double sided tape	6	3	Rigid PVC	30	40	30	40	2,653	39199080	1000
15181GY	-30	60	Grey	Acrylic double sided tape	6	3	Rigid PVC	30	50	30	50	2,720	39199080	1001
15184GY	-30	60	Grey	Acrylic double sided tape	4	2	Rigid PVC	60	62	60	62	4,040	39199080	1003
15194	-30	60	White	Acrylic double sided tape	4	2	Rigid PVC10050WH	60	62	60	62	4,040	39199080	1003
15104	-30	60	Black RAL 9005	Acrylic double sided tape	4	2	Rigid PVC	62	62	60	62	4,220	39199080	1003
15164	-30	60	Blue	Acrylic double sided tape	4	2	Rigid PVC	62	62	60	62	3,953	39199080	1003
15144	-30	60	Yellow	Acrylic double sided tape	4	2	Rigid PVC10050YE	60	62	60	62	4,500	39199080	1003
15124	-30	60	Rosso	Acrylic double sided tape	4	2	Rigid PVC	60	62	60	62	4,480	39199080	1003

tipo	Minimum application temperature [°c]	Maximum application temperature [°c]	Colour	Type of adhesive	Sheet elements	Number of columns	Material	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Customs code	Software code
15192	-30	60	White	Acrylic double sided tape	6	3	Rigid PVC10050WH	30	39	30	39	2,790	39199080	1002
15197	-30	60	White	Acrylic double sided tape	4	2	Rigid PVC10050WH	40	60	40	60	4,360	39199080	1005
15102	-30	60	Black RAL 9005	Acrylic double sided tape	6	3	Rigid PVC	30	39	30	39	2,760	39199080	1002
15198	-30	60	White	Acrylic double sided tape	4	2	Rigid PVC10050WH	60	62	60	62	4,440	39199080	1004
15108	-30	60	Black RAL 9005	Acrylic double sided tape	4	2	Rigid PVC	60	62	60	62	4,540	39199080	1004
15121	-30	60	Rosso	Acrylic double sided tape	6	3	Rigid PVC	50	30	30	50	2,547	39199080	1001
15122	-30	60	Rosso	Acrylic double sided tape	6	3	Rigid PVC	30	39	30	39	2,667	39199080	1002
15142	-30	60	Yellow	Acrylic double sided tape	6	3	Rigid PVC10050YE	30	39	30	39	2,627	39199080	1002
15182GY	-30	60	Grey	Acrylic double sided tape	6	3	Rigid PVC	30	39	30	39	2,417	39199080	1002
15187GY	-30	60	Grey	Acrylic double sided tape	4	2	Rigid PVC	40	60	40	60	4,220	39199080	1005
15199	-30	60	White	Acrylic double sided tape	6	3	Rigid PVC10050WH	50	50	30	50	2,410	39199080	1006
15297	-30	60	White	Acrylic double sided tape	6	3	Rigid PVC10050WH	30	39	30	39	2,431	39199080	1007