

MG-TAA

ADHESIVE TAGS FOR COMPONENTS, PRE-CUT, RIGID PVC



CERTIFICATIONS & APPROVALS

 UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-30 °C
Maximum operating temperature	60 °C
Type of adhesive	acrylic double sided tape
Self-extinguishing fire class according to UL 94	V0

MATERIAL COMPOSITION AND TREATMENTS

Silicone-free

Yes

LOGISTIC

Customs code	39199080
--------------	----------

MG-TAA

tipo	Minimum application temperature [°c]	Maximum application temperature [°c]	Colour	Type of application surface	Sheet elements	Number of lines	Number of columns	Material	Halogen free	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	Software code	ETIM C
49115	-30	60	Black RAL 9005	smooth flat	14	2	7	Rigid PVC	No	15	67	67	15	1,495	10 ÷ 25	45 ÷ 55	977	Label mate [EC00
49405CY	-30	60	Grey	smooth flat	14	2	7	Rigid PVC	No	15	67	67	15	1,306	10 ÷ 25	45 ÷ 55	977	Label mate [EC00
49192N	-30	60	White	smooth flat	42	6	7	Rigid PVC10050WH	No	20	17	17	15	0,432	10 ÷ 25	45 ÷ 55	965	Label mate [EC00
49393	-30	60	White	smooth flat	12	2	6	Rigid PVC10050WH	No	17	44	44	17	1,493	10 ÷ 25	45 ÷ 55	717	Label mate [EC00
49292	-30	60	White	smooth flat	10	2	5	Rigid PVC10050WH	No	20	40	40	20	1,816	10 ÷ 25	45 ÷ 55	803	Label mate [EC00
49293	-30	60	White	smooth flat	10	2	5	Rigid PVC10050WH	No	20	48	48	20	1,776	10 ÷ 25	45 ÷ 55	850	Label mate [EC00
49294	-30	60	White	smooth flat	5	1	5	Rigid PVC10050WH	No	20	72	72	20	3,288	10 ÷ 25	45 ÷ 55	851	Label mate [EC00
49295	-30	60	White	smooth flat	5	1	5	Rigid PVC10050WH	No	20	96	96	20	3,694	10 ÷ 25	45 ÷ 55	852	Label mate [EC00
49296	-30	60	White	smooth flat	96	8	12	Rigid PVC10050WH	No	8	12	12	8	0,188	10 ÷ 25	45 ÷ 55	723	Label mate [EC00
49142N	-30	60	Yellow	smooth flat	42	6	7	Rigid PVC10050YE	No	15	17	17	15	0,434	10 ÷ 25	45 ÷ 55	965	Label mate [EC00
49343	-30	60	Yellow	smooth flat	12	2	6	Rigid PVC10050YE	No	17	44	44	17	1,500	10 ÷ 25	45 ÷ 55	717	Label mate [EC00
49204	-30	60	Black RAL 9005	smooth flat	5	1	5	Rigid PVC	No	20	72	72	20	3,344	10 ÷ 25	45 ÷ 55	851	Label mate [EC00
49104N	-30	60	Black RAL 9005	smooth flat	14	2	7	Rigid PVC	No	15	49	49	15	1,360	10 ÷ 25	45 ÷ 55	967	Label mate [EC00
49263	-30	60	Blue	smooth flat	10	2	5	Rigid PVC	No	20	48	48	20	1,904	10 ÷ 25	45 ÷ 55	850	Label mate [EC00
49319N	-30	60	Black RAL 9005	smooth flat	28	8	4	Rigid PVC	No	9	15	26	12	0,664	10 ÷ 25	45 ÷ 55	862	Label mate [EC00
49310	-30	60	Black RAL 9005	smooth flat	9	3	3	Rigid PVC	No	27	27	27	27	2,107	10 ÷ 25	45 ÷ 55	863	Label mate [EC00
49319	-30	60	Black RAL 9005	smooth flat	15	3	5	Rigid PVC	No	12.5	27	27	12.5	1,275	10 ÷ 25	45 ÷ 55	865	Label mate [EC00
49316	-30	60	Black RAL 9005	smooth flat	20	4	5	Rigid PVC	No	18	27	27	18	0,952	10 ÷ 25	45 ÷ 55	178	Label mate [EC00
49156	-30	60	Green	smooth flat	60	5	12	Rigid PVC	No	7	20	20	7	0,316	10 ÷ 25	45 ÷ 55	179	Label mate [EC00
49256	-30	60	Green	smooth flat	96	8	12	Rigid PVC	No	8	12	12	8	0,198	10 ÷ 25	45 ÷ 55	723	Label mate [EC00
49250N	-30	60	Green	smooth flat	88	8	11	Rigid PVC	No	9	12	12	9	0,187	10 ÷ 25	45 ÷ 55	960	Label mate [EC00
49357N	-30	60	Green	smooth flat	77	7	11	Rigid PVC	No	9	15	15	9	0,217	10 ÷ 25	45 ÷ 55	961	Label mate [EC00
49150N	-30	60	Green	smooth flat	55	5	11	Rigid PVC	No	9	20	20	9	0,349	10 ÷ 25	45 ÷ 55	962	Label mate [EC00
49151N	-30	60	Green	smooth flat	33	3	11	Rigid PVC	No	9	35	35	9	0,555	10 ÷ 25	45 ÷ 55	964	Label mate [EC00
49118	-30	60	Black RAL 9005	smooth flat	18	3	6	Rigid PVC	No	17	35	35	17	1,058	10 ÷ 25	45 ÷ 55	711	Label mate [EC00
49128	-30	60	Rosso	smooth flat	18	3	6	Rigid PVC	No	17	35	35	17	1,067	10 ÷ 25	45 ÷ 55	711	Label mate [EC00
49157	-30	60	Green	smooth flat	20	2	10	Rigid PVC	No	9	50	50	9	0,823	10 ÷ 25	45 ÷ 55	976	Label mate [EC00

tipo	Minimum application temperature [°c]	Maximum application temperature [°c]	Colour	Type of application surface	Sheet elements	Number of lines	Number of columns	Material	Halogen free	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	Software code	ETIM C
49152N	-30	60	Green	smooth flat	42	6	7	Rigid PVC	No	15	17	17	15	0,450	10 ÷ 25	45 ÷ 55	965	Label mate [EC00
49153N	-30	60	Green	smooth flat	28	4	7	Rigid PVC	No	15	27	27	15	0,590	10 ÷ 25	45 ÷ 55	966	Label mate [EC00
49258	-30	60	Green	smooth flat	12	2	6	Rigid PVC	No	15	44	44	15	1,527	10 ÷ 25	45 ÷ 55	854	Label mate [EC00
49154N	-30	60	Green	smooth flat	14	2	7	Rigid PVC	No	15	49	49	15	1,174	10 ÷ 25	45 ÷ 55	967	Label mate [EC00
49158	-30	60	Green	smooth flat	18	3	6	Rigid PVC	No	17	35	35	17	1,040	10 ÷ 25	45 ÷ 55	711	Label mate [EC00
49353	-30	60	Green	smooth flat	12	2	6	Rigid PVC	No	17	44	44	17	1,573	10 ÷ 25	45 ÷ 55	717	Label mate [EC00
49252	-30	60	Green	smooth flat	10	2	5	Rigid PVC	No	20	40	40	20		10 ÷ 25	45 ÷ 55	803	Label mate [EC00
49253	-30	60	Green	smooth flat	10	2	5	Rigid PVC	No	20	48	48	20	1,904	10 ÷ 25	45 ÷ 55	850	Label mate [EC00
49254	-30	60	Green	smooth flat	5	1	5	Rigid PVC	No	20	72	72	20	3,824	10 ÷ 25	45 ÷ 55	851	Label mate [EC00
49255	-30	60	Green	smooth flat	5	1	5	Rigid PVC	No	20	96	96	20	3,600	10 ÷ 25	45 ÷ 55	852	Label mate [EC00
49106GY	-30	60	Grey	smooth flat	60	5	12	Rigid PVC	No	7	20	20	7	0,303	10 ÷ 25	45 ÷ 55	179	Label mate [EC00
49206GY	-30	60	Grey	smooth flat	96	8	12	Rigid PVC	No	9	12	12	8	0,171	10 ÷ 25	45 ÷ 55	723	Label mate [EC00
49400NGY	-30	60	Grey	smooth flat	88	8	11	Rigid PVC	No	9	12	12	9	0,215	10 ÷ 25	45 ÷ 55	960	Label mate [EC00
49307NGY	-30	60	Grey	smooth flat	77	7	11	Rigid PVC	No	9	15	15	9	0,215	10 ÷ 25	45 ÷ 55	961	Label mate [EC00
49100NGY	-30	60	Grey	smooth flat	55	5	11	Rigid PVC	No	9	20	20	9	0,335	10 ÷ 25	45 ÷ 55	962	Label mate [EC00
49101NGY	-30	60	Grey	smooth flat	33	3	11	Rigid PVC	No	9	35	35	9	0,567	10 ÷ 25	45 ÷ 55	964	Label mate [EC00
49107GY	-30	60	Grey	smooth flat	20	2	10	Rigid PVC	No	9	50	50	9	0,796	10 ÷ 25	45 ÷ 55	976	Label mate [EC00
49156SGN	-30	60	Siemens green	smooth flat	60	5	12	Rigid PVC	No	7	20	20	7	0,300	10 ÷ 25	45 ÷ 55	179	Label mate [EC00
49102NGY	-30	60	Grey	smooth flat	42	6	7	Rigid PVC	No	15	17	17	15	0,434	10 ÷ 25	45 ÷ 55	965	Label mate [EC00
49103NGY	-30	60	Grey	smooth flat	28	4	7	Rigid PVC	No	15	27	27	15	0,683	10 ÷ 25	45 ÷ 55	966	Label mate [EC00
49208GY	-30	60	Grey	smooth flat	12	2	6	Rigid PVC	No	9	44	44	15	1,540	10 ÷ 25	45 ÷ 55	854	Label mate [EC00
49304NGY	-30	60	Grey	smooth flat	14	2	7	Rigid PVC	No	15	49	49	15	1,197	10 ÷ 25	45 ÷ 55	967	Label mate [EC00
49408GY	-30	60	Grey	smooth flat	18	3	6	Rigid PVC	No	17	35	35	17	1,036	10 ÷ 25	45 ÷ 55	711	Label mate [EC00
49303GY	-30	60	Grey	smooth flat	12	2	6	Rigid PVC	No	17	44	44	17	1,400	10 ÷ 25	45 ÷ 55	717	Label mate [EC00
49202GY	-30	60	Grey	smooth flat	10	2	5	Rigid PVC	No	9	40	40	20	1,856	10 ÷ 25	45 ÷ 55	803	Label mate [EC00
49203GY	-30	60	Grey	smooth flat	10	2	5	Rigid PVC	No	9	48	48	20	1,856	10 ÷ 25	45 ÷ 55	850	Label mate [EC00
49504GY	-30	60	Grey	smooth flat	5	1	5	Rigid PVC	No	20	72	72	20	3,648	10 ÷ 25	45 ÷ 55	851	Label mate [EC00
49205GY	-30	60	Grey	smooth flat	5	1	5	Rigid PVC	No	9	96	96	20	3,232	10 ÷ 25	45 ÷ 55	852	Label mate [EC00

tipo	Minimum application temperature [°c]	Maximum application temperature [°c]	Colour	Type of application surface	Sheet elements	Number of lines	Number of columns	Material	Halogen free	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	Software code	ETIM C
49116	-30	60	Black RAL 9005	smooth flat	60	5	12	Rigid PVC	No	7	20	20	7	0,309	10 ÷ 25	45 ÷ 55	179	Label mate [EC00
49216	-30	60	Black RAL 9005	smooth flat	96	8	12	Rigid PVC	No	8	12	12	8	0,193	10 ÷ 25	45 ÷ 55	723	Label mate [EC00
49210N	-30	60	Black RAL 9005	smooth flat	88	8	11	Rigid PVC	No	9	12	12	9	0,216	10 ÷ 25	45 ÷ 55	960	Label mate [EC00
49193N	-30	60	White	smooth flat	28	4	7	Rigid PVC10050WH	No	8	27	27	15	0,593	10 ÷ 25	45 ÷ 55	966	Label mate [EC00
49317N	-30	60	Black RAL 9005	smooth flat	77	7	11	Rigid PVC	No	9	15	15	9	0,241	10 ÷ 25	45 ÷ 55	961	Label mate [EC00
49110N	-30	60	Black RAL 9005	smooth flat	55	5	11	Rigid PVC	No	9	20	20	9	0,343	10 ÷ 25	45 ÷ 55	962	Label mate [EC00
49111N	-30	60	Black RAL 9005	smooth flat	33	3	11	Rigid PVC	No	9	35	35	9	0,509	10 ÷ 25	45 ÷ 55	964	Label mate [EC00
49117	-30	60	Black RAL 9005	smooth flat	20	2	10	Rigid PVC	No	9	50	50	9	0,955	10 ÷ 25	45 ÷ 55	976	Label mate [EC00
49112N	-30	60	Black RAL 9005	smooth flat	42	6	7	Rigid PVC	No	15	17	17	15	0,459	10 ÷ 25	45 ÷ 55	965	Label mate [EC00
49113N	-30	60	Black RAL 9005	smooth flat	28	4	7	Rigid PVC	No	15	27	27	15	0,677	10 ÷ 25	45 ÷ 55	966	Label mate [EC00
49218	-30	60	Black RAL 9005	smooth flat	12	2	6	Rigid PVC	No	15	44	44	15	1,376	10 ÷ 25	45 ÷ 55	854	Label mate [EC00
49143N	-30	60	Yellow	smooth flat	28	4	7	Rigid PVC10050YE	No	15	27	27	15	0,651	10 ÷ 25	45 ÷ 55	966	Label mate [EC00
49313	-30	60	Black RAL 9005	smooth flat	12	2	6	Rigid PVC	No	17	44	44	17		10 ÷ 25	45 ÷ 55	717	Label mate [EC00
49212	-30	60	Black RAL 9005	smooth flat	10	2	5	Rigid PVC	No	20	40	40	20	1,776	10 ÷ 25	45 ÷ 55	803	Label mate [EC00
49213	-30	60	Black RAL 9005	smooth flat	10	2	5	Rigid PVC	No	20	48	48	20	1,832	10 ÷ 25	45 ÷ 55	850	Label mate [EC00
49215	-30	60	Black RAL 9005	smooth flat	5	1	5	Rigid PVC	No	20	96	96	20	3,360	10 ÷ 25	45 ÷ 55	852	Label mate [EC00
49126	-30	60	Rosso	smooth flat	60	5	12	Rigid PVC	No	7	20	20	7	0,323	10 ÷ 25	45 ÷ 55	179	Label mate [EC00
49226	-30	60	Rosso	smooth flat	96	8	12	Rigid PVC	No	8	12	12	8	0,200	10 ÷ 25	45 ÷ 55	723	Label mate [EC00
49220N	-30	60	Rosso	smooth flat	88	8	11	Rigid PVC	No	27	12	12	9	0,207	10 ÷ 25	45 ÷ 55	960	Label mate [EC00
49327N	-30	60	Rosso	smooth flat	77	7	11	Rigid PVC	No	9	15	15	9	0,240	10 ÷ 25	45 ÷ 55	961	Label mate [EC00
49120N	-30	60	Rosso	smooth flat	55	5	11	Rigid PVC	No	9	20	20	9	0,327	10 ÷ 25	45 ÷ 55	962	Label mate [EC00
49121N	-30	60	Rosso	smooth flat	33	3	11	Rigid PVC	No	9	35	35	9	0,621	10 ÷ 25	45 ÷ 55	964	Label mate [EC00
49127	-30	60	Rosso	smooth flat	20	2	10	Rigid PVC	No	9	50	50	9	0,900	10 ÷ 25	45 ÷ 55	976	Label mate [EC00
49122N	-30	60	Rosso	smooth flat	42	6	7	Rigid PVC	No	15	17	17	15	0,427	10 ÷ 25	45 ÷ 55	965	Label mate [EC00
49123N	-30	60	Rosso	smooth flat	28	4	7	Rigid PVC	No	15	27	27	15	0,674	10 ÷ 25	45 ÷ 55	966	Label mate [EC00
49228	-30	60	Rosso	smooth flat	12	2	6	Rigid PVC	No	15	44	44	15	1,553	10 ÷ 25	45 ÷ 55	854	Label mate [EC00
49124N	-30	60	Rosso	smooth flat	14	2	7	Rigid PVC	No	15	49	49	15	1,217	10 ÷ 25	45 ÷ 55	967	Label mate [EC00
49323	-30	60	Rosso	smooth flat	12	2	6	Rigid PVC	No	17	44	44	17	1,393	10 ÷ 25	45 ÷ 55	717	Label mate [EC00

tipo	Minimum application temperature [°c]	Maximum application temperature [°c]	Colour	Type of application surface	Sheet elements	Number of lines	Number of columns	Material	Halogen free	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	Software code	ETIM C
49222	-30	60	Rosso	smooth flat	10	2	5	Rigid PVC	No	20	40	40	20	1,840	10 ÷ 25	45 ÷ 55	803	Label mate [EC00
49223	-30	60	Rosso	smooth flat	10	2	5	Rigid PVC	No	20	48	48	20	1,888	10 ÷ 25	45 ÷ 55	850	Label mate [EC00
49224	-30	60	Rosso	smooth flat	5	1	5	Rigid PVC	No	20	72	72	20	3,728	10 ÷ 25	45 ÷ 55	851	Label mate [EC00
49225	-30	60	Rosso	smooth flat	5	1	5	Rigid PVC	No	20	96	96	20	3,690	10 ÷ 25	45 ÷ 55	852	Label mate [EC00
49166	-30	60	Blue	smooth flat	60	5	12	Rigid PVC	No	7	20	20	7	0,316	10 ÷ 25	45 ÷ 55	179	Label mate [EC00
49266	-30	60	Blue	smooth flat	96	8	12	Rigid PVC	No	8	12	12	8	0,195	10 ÷ 25	45 ÷ 55	723	Label mate [EC00
49260N	-30	60	Blue	smooth flat	88	8	11	Rigid PVC	No	9	12	12	9	0,207	10 ÷ 25	45 ÷ 55	960	Label mate [EC00
49367N	-30	60	Blue	smooth flat	77	7	11	Rigid PVC	No	9	15	15	9	0,236	10 ÷ 25	45 ÷ 55	961	Label mate [EC00
49160N	-30	60	Blue	smooth flat	55	5	11	Rigid PVC	No	9	20	20	9	0,337	10 ÷ 25	45 ÷ 55	962	Label mate [EC00
49161N	-30	60	Blue	smooth flat	33	3	11	Rigid PVC	No	9	35	35	9	0,565	10 ÷ 25	45 ÷ 55	964	Label mate [EC00
49167	-30	60	Blue	smooth flat	20	2	10	Rigid PVC	No	9	50	50	9	0,876	10 ÷ 25	45 ÷ 55	976	Label mate [EC00
49162N	-30	60	Blue	smooth flat	42	6	7	Rigid PVC	No	15	17	17	15	0,450	10 ÷ 25	45 ÷ 55	965	Label mate [EC00
49163N	-30	60	Blue	smooth flat	28	4	7	Rigid PVC	No	15	27	27	15	0,660	10 ÷ 25	45 ÷ 55	966	Label mate [EC00
49268	-30	60	Blue	smooth flat	12	2	6	Rigid PVC	No	15	44	44	15	1,508	10 ÷ 25	45 ÷ 55	854	Label mate [EC00
49527	-30	60	Rosso	smooth flat	24	14	2	Rigid PVC	No	7	44	44	7	0,767	10 ÷ 25	45 ÷ 55	795	Label mate [EC00
49168	-30	60	Blue	smooth flat	18	3	6	Rigid PVC	No	17	35	35	17	1,049	10 ÷ 25	45 ÷ 55	711	Label mate [EC00
49363	-30	60	Blue	smooth flat	12	2	6	Rigid PVC	No	17	44	44	17		10 ÷ 25	45 ÷ 55	717	Label mate [EC00
49262	-30	60	Blue	smooth flat	10	2	5	Rigid PVC	No	20	40	40	20	1,984	10 ÷ 25	45 ÷ 55	803	Label mate [EC00
49567	-30	60	Blue	smooth flat	24	14	2	Rigid PVC	No	7	44	44	7	0,800	10 ÷ 25	45 ÷ 55	795	Label mate [EC00
49264	-30	60	Blue	smooth flat	5	1	5	Rigid PVC	No	20	72	72	20	3,754	10 ÷ 25	45 ÷ 55	851	Label mate [EC00
49265	-30	60	Blue	smooth flat	5	1	5	Rigid PVC	No	20	96	96	20	3,584	10 ÷ 25	45 ÷ 55	852	Label mate [EC00
49194N	-30	60	White	smooth flat	14	2	7	Rigid PVC10050WH	No	15	49	49	15	1,180	10 ÷ 25	45 ÷ 55	967	Label mate [EC00
49597	-30	60	White	smooth flat	24	14	2	Rigid PVC10050WH	No	7	44	44	7	0,666	10 ÷ 25	45 ÷ 55	795	Label mate [EC00
49598	-30	60	White		12			Rigid PVC		22	27	22	22	1,500			969	Label mate [EC00
49599	-30	60	White	smooth flat	84	12	7	Rigid PVC10050WH	No	5	10	10	5	0,200	10 ÷ 25	45 ÷ 55	959	Label mate [EC00
49144N	-30	60	Yellow	smooth flat	14	2	7	Rigid PVC10050YE	No	15	49	49	15	1,320	10 ÷ 25	45 ÷ 55	967	Label mate [EC00
49398N	-30	60	White	smooth flat	25	5	5	Rigid PVC10050WH	No	21	21	21	21	0,733	10 ÷ 25	45 ÷ 55	956	Label mate [EC00
49348N	-30	60	Yellow	smooth flat	25	5	5	Rigid PVC10050YE	No	21	21	21	21	0,736	10 ÷ 25	45 ÷ 55	866	Label mate [EC00

tipo	Minimum application temperature [°c]	Maximum application temperature [°c]	Colour	Type of application surface	Sheet elements	Number of lines	Number of columns	Material	Halogen free	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	Software code	ETIM C
49614	-30	60	Black RAL 9005	smooth flat	9	3	3	Rigid PVC	No	17,5	27	17,5	27	1,956	10 ÷ 25	45 ÷ 55		
49644	-30	60	Yellow	smooth flat	9	3	3	Rigid PVC10050YE	No	17,5	27	17,5	27	1,956	10 ÷ 25	45 ÷ 55		
49191N	-30	60	White	smooth flat	33	3	11	Rigid PVC10050WH	No	9	35	35	9	0,506	10 ÷ 25	45 ÷ 55	964	Label mate [EC00
49241	-30	60	Yellow	smooth flat	18	3	6	Rigid PVC10050YE	No	17	32	32	17	0,884	10 ÷ 25	45 ÷ 55	710	Label mate [EC00
49291	-30	60	White	smooth flat	18	3	6	Rigid PVC10050WH	No	17	32	32	17	1,020	10 ÷ 25	45 ÷ 55	710	Label mate [EC00
49141N	-30	60	Yellow	smooth flat	33	3	11	Rigid PVC10050YE	No	9	35	35	9	0,550	10 ÷ 25	45 ÷ 55	964	Label mate [EC00
49196	-30	60	White	smooth flat	60	5	12	Rigid PVC10050WH	No	7	20	20	7	0,303	10 ÷ 25	45 ÷ 55	179	Label mate [EC00
49148	-30	60	Yellow	smooth flat	18	3	6	Rigid PVC10050YE	No	17	35	35	17	1,009	10 ÷ 25	45 ÷ 55	711	Label mate [EC00
49198	-30	60	White	smooth flat	18	3	6	Rigid PVC10050WH	No	17	35	35	17	1,013	10 ÷ 25	45 ÷ 55	711	Label mate [EC00
49149	-30	60	Yellow	smooth flat	10	10	1	Rigid PVC10050YE	No	10	105	105	10	1,800	10 ÷ 25	45 ÷ 55	530	Label mate [EC00
49199	-30	60	White	smooth flat	10	10	1	Rigid PVC10050WH	No	10	105	105	10	1,856	10 ÷ 25	45 ÷ 55	530	Label mate [EC00
49197	-30	60	White	smooth flat	20	2	10	Rigid PVC10050WH	No	9	50	50	9	0,908	10 ÷ 25	45 ÷ 55	976	Label mate [EC00
49549	-30	60	Yellow	smooth flat	84	12	7	Rigid PVC10050YE	No	5	10	10	5	0,216	10 ÷ 25	45 ÷ 55	959	Label mate [EC00
49547	-30	60	Yellow	smooth flat	24	14	2	Rigid PVC10050YE	No	7	44	44	7	0,760	10 ÷ 25	45 ÷ 55	795	Label mate [EC00
49596	-30	60	White	smooth flat	12	3	4	Rigid PVC10050WH	No	25	35	35	25	1,533	10 ÷ 25	45 ÷ 55	848	Label mate [EC00
49595	-30	60	White	smooth flat	12	3	4	Rigid PVC10050WH	No	25	32	32	25	1,523	10 ÷ 25	45 ÷ 55	847	Label mate [EC00
49498	-30	60	White	smooth flat	33	3	11	Rigid PVC10050WH	No	8,5	30	30	8,5	0,504	10 ÷ 25	45 ÷ 55	720	Label mate [EC00
49448	-30	60	Yellow	smooth flat	33	3	11	Rigid PVC10050YE	No	8,5	30	30	8,5	0,543	10 ÷ 25	45 ÷ 55	720	Label mate [EC00
49248	-30	60	Yellow	smooth flat	12	2	6	Rigid PVC10050YE	No	15	44	44	15	1,374	10 ÷ 25	45 ÷ 55	854	Label mate [EC00
49246	-30	60	Yellow	smooth flat	96	8	12	Rigid PVC10050YE	No	8	12	12	8	0,173	10 ÷ 25	45 ÷ 55	723	Label mate [EC00
49245	-30	60	Yellow	smooth flat	5	1	5	Rigid PVC10050YE	No	20	96	96	20	3,216	10 ÷ 25	45 ÷ 55	852	Label mate [EC00
49244	-30	60	Yellow	smooth flat	5	1	5	Rigid PVC10050YE	No	20	72	72	20	3,664	10 ÷ 25	45 ÷ 55	851	Label mate [EC00
49243	-30	60	Yellow	smooth flat	10	2	5	Rigid PVC10050YE	No	20	48	48	20	1,824	10 ÷ 25	45 ÷ 55	850	Label mate [EC00
49242	-30	60	Yellow	smooth flat	10	2	5	Rigid PVC10050YE	No	20	40	40	20	1,651	10 ÷ 25	45 ÷ 55	803	Label mate [EC00
49346	-30	60	Yellow	smooth flat	20	4	5	Rigid PVC10050YE	No	18	27	27	18	0,932	10 ÷ 25	45 ÷ 55	178	Label mate [EC00
49396	-30	60	White	smooth flat	20	4	5	Rigid PVC10050WH	No	18	27	27	18	0,896	10 ÷ 25	45 ÷ 55	178	Label mate [EC00
49390	-30	60	White	smooth flat	9	3	3	Rigid PVC10050WH	No	27	27	27	27	2,053	10 ÷ 25	45 ÷ 55	863	Label mate [EC00
49399	-30	60	White	smooth flat	15	3	5	Rigid PVC10050WH	No	12,5	27	27	12,5	1,152	10 ÷ 25	45 ÷ 55	865	Label mate [EC00

tipo	Minimum application temperature [°C]	Maximum application temperature [°C]	Colour	Type of application surface	Sheet elements	Number of lines	Number of columns	Material	Halogen free	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Storage temperature [°C]	Relative humidity of storage	Software code	ETIM C
49347N	-30	60	Yellow	smooth flat	77	7	11	Rigid PVC10050YE	No	9	15	15	9	0,237	10 ÷ 25	45 ÷ 55	961	Label mate [EC00
49397N	-30	60	White	smooth flat	77	7	11	Rigid PVC10050WH	No	9	15	15	9	0,236	10 ÷ 25	45 ÷ 55	961	Label mate [EC00
49493	-30	60	White	smooth flat	72	6	12	Rigid PVC10050WH	No	8	17	17	8	0,250	10 ÷ 25	45 ÷ 55	724	Label mate [EC00
49399N	-30	60	White	smooth flat	28	4	7	Rigid PVC10050WH	No	12	26	26	12	0,648	10 ÷ 25	45 ÷ 55	862	Label mate [EC00
49495	-30	60	White	smooth flat	49	7	7	Rigid PVC10050WH	No	15	15	15	15	0,398	10 ÷ 25	45 ÷ 55	183	Label mate [EC00
49445	-30	60	Yellow	smooth flat	49	7	7	Rigid PVC10050YE	No	15	15	15	15	0,347	10 ÷ 25	45 ÷ 55	183	Label mate [EC00
49443	-30	60	Yellow	smooth flat	72	6	12	Rigid PVC10050YE	No	8	17	17	8	0,248	10 ÷ 25	45 ÷ 55	724	Label mate [EC00
49695	-30	60	White	smooth flat	9	3	3	Rigid PVC10050WH	No	22	22	22	22	1,730	10 ÷ 25	45 ÷ 55		
49694	-30	60	White	smooth flat	9	3	3	Rigid PVC10050WH	No	17.5	27	17.5	27	2,044	10 ÷ 25	45 ÷ 55		
49508GY			Grey		12			Rigid PVC		0.5	27			1,520			969	Label mate [EC00