


MG-VCT

ADHESIVE LABELS FOR COMPONENTS, PRE-CUT, ACRYLIC-COATED COTTON FABRIC



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	150 °C
Minimum application temperature	10 °C
Maximum application temperature	40 °C
Type of adhesive	adhesive film
Type of application surface	flat; curved

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39199080

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4
Plates	MG2-PLT

MATERIAL COMPOSITION AND TREATMENTS

Material	Cotton fabric coated with acrylic
Silicone-free	Yes
Halogen free	No

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

MG-VCT

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
48040	Yellow	105	7	15	6	15	15	6	0,076	181
48041	Yellow	120	10	12	7	10	10	7	0,067	191
48045	Yellow	70	7	10	9	15	15	9	0,114	161
48046N	Yellow	55	5	11	9	20	20	9	0,140	162
48047	Yellow	27	3	9	11	38	38	11	0,298	184
48014	yellow	80	8	10	9	12	12	9	0,094	160
48090	White	105	7	15	6	15	15	6	0,077	181
48091	White	120	10	12	7	10	10	7	0,066	191
48097	White	27	3	9	11	38	38	11	0,307	184
48095	White	70	7	10	9	15	15	9	0,116	161
48096N	White	55	5	11	9	20	20	9		162