

MG-VRT-A-HF

ADHESIVE PANEL PLATES, PRE-CUT, POLYCARBONATE, HALOGEN FREE



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	120 °C
Minimum application temperature	10 °C
Maximum application temperature	40 °C
Type of adhesive	Acrylic double sided tape
Type of application surface	flat smooth
Self-extinguishing fire class according to UL 94	V0

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39199080

COMPATIBILITY

Ribbon	MG2-EPTR PREMIUM
Printable with	MG3; MG4
Plates	MG2-PLT

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

MG-VRT-A-HF

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
88904-HF	White	1	1	1	105	110	110	105	16,828	812
88903-HF	White	2	1	2	52	107	107	52	7,520	204
88928-HF	White	1	1	1	102	138	138	102	18,760	207
88901-HF	White	2	1	2	42	78	78	42	7,600	202
88701-HF	Metallic grey	2	1	2	42	78	78	42	7,600	202
88702-HF	Metallic grey	1	1	1	62	88	88	62	14,764	203
88769-HF	Metallic grey	2	1	2	50	100	100	50	7,564	844
88777-HF	Metallic grey	1	1	1	100	140	140	100	17,092	838
88762-HF	Metallic grey	2	2	1	60	100	100	60	8,520	821
88703-HF	Metallic grey	2	1	2	52	107	107	52	7,556	204
88735-HF	Metallic grey	2	1	2	40	138	138	40	8,220	822
88771-HF	Metallic grey	2	2	2	57	82.5	82.5	57	8,440	841
88765-HF	Metallic grey	5	1	5	20	110	110	20	3,488	779
88704-HF	Metallic grey	1	1	1	105	110	110	105	16,440	812
88717-HF	Metallic grey	3	1	3	35	100	100	35	5,067	810
88708-HF	Metallic grey	4	1	4	25	80	80	25	3,844	861
88716-HF	Metallic grey	8	2	4	25	50	50	25	1,900	853
88713-HF	Metallic grey	1	1	1	92	118	92	118	15,300	813
88728-HF	Metallic grey	1	1	1	102	138	138	102	17,004	207
88700N-HF	Metallic grey	6	2	3	32	58	58	32	2,796	200