

RT-TAP



Features

TECHNICAL INFORMATION

Maximum operating temperature	90 °C
Minimum application temperature	10 °C
Maximum application temperature	40 °C
Self-extinguishing fire class according to UL 94	V0

WEIGHT AND DIMENSIONS

Width	15 mm
-------	-------

MATERIAL COMPOSITION AND TREATMENTS

Material	Rigid dielectric high-impact PVC
Silicone-free	No
Halogen free	No

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39269097

RTA-TAP

tipo	Colour	Type of adhesive	Type of application surface	L [mm]	Gross weight [g]	ETIM Class 7
990455N	Black RAL 9005	Spongy double sided tape	flat smooth	430	21,400	Mounting for labelling material [EC002248]
990665N	Black RAL 9005	Spongy double sided tape	flat smooth	650	48,000	Labelling material [EC001288]
990525N	Black RAL 9005	Spongy double sided tape	flat smooth	1000	47,560	Labelling material [EC001288]
990453N	Grey RAL 7047	Spongy double sided tape	flat smooth	430	20,200	Mounting for labelling material [EC002248]
990663N	Grey RAL 7047	Spongy double sided tape	flat smooth	430		Mounting for labelling material [EC002248]
990503N	Grey RAL 7047	Spongy double sided tape	flat smooth	1000	47,560	Mounting for labelling material [EC002248]

RT-TAP RT-CCP

tipo	Colour	L [mm]	Gross weight [g]	ETIM Class 7
990456	Transparent	430	16,000	Mounting for labelling material [EC002248]

RTR-TAP

tipo	Colour	Type of application surface	L [mm]	Gross weight [g]	ETIM Class 7
990502	Grey RAL 7047	flat smooth	1000	38,272	Mounting for labelling material [EC002248]
990452	Grey RAL 7047	flat smooth	430	19,600	Mounting for labelling material [EC002248]
990662	Grey RAL 7047	flat smooth	650	38,000	Mounting for labelling material [EC002248]
990524	Black RAL 9005	flat smooth	1000	41,680	Mounting for labelling material [EC002248]
990454	Black RAL 9005	flat smooth	430	19,120	Mounting for labelling material [EC002248]
990664	Black RAL 9005	flat smooth	650	0,737	Mounting for labelling material [EC002248]