

MG-TDMO



Features

TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	130 °C
Self-extinguishing fire class according to UL 94	V0
Sheet elements	40
Number of lines	4
Number of columns	10

WEIGHT AND DIMENSIONS

Width	4 mm
Height of the printable area	4 mm

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

MATERIAL COMPOSITION AND TREATMENTS

Material	Polycarbonate
Silicone-free	Yes
Halogen free	Yes

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39269097

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4
Plates	MG2-PTM

MG-TDMO-01

Range of cable housing diameter
2 ÷ 2.9 mm

Range of cable cross section
0.5 ÷ 1.5 mm²

tipo	Colour	L [mm]	Base of the printable area [mm]	Gross weight [g]	Software code
40390	White	12	12	0,374	125
40391	White	16	16	0,368	128
40340	Yellow	12	12		125
40341	Yellow	16	16		128

MG-TDMO-02

Range of cable housing diameter
2.9 ÷ 3.5 mm

Range of cable cross section
1.5 ÷ 2.5 mm²

tipo	Colour	L [mm]	Base of the printable area [mm]	Gross weight [g]	Software code
40491	White	16	16	0,381	129
40490	White	12	12	0,369	126
40441	Yellow	16	16	0,369	129
40440	Yellow	12	12	0,369	126

MG-TDMO-03

Range of cable housing diameter
4 ÷ 4.6 mm

Range of cable cross section
4 ÷ 6 mm²

tipo	Colour	L [mm]	Base of the printable area [mm]	Gross weight [g]	Software code
40591	White	16	16	0,396	130
40590	White	12	12	0,389	127
40541	Yellow	16	16	0,407	130
40540	Yellow	12	12	0,396	127