

ETF-ROLL-SBS

TIE-ON CABLE TAGS, PRE-CUT, WITHOUT HOLDER, STYRENE-BUTADIENE-STYRENE, WITHOUT HOLDER, HALOGEN FREE



Features

TECHNICAL INFORMATION

Minimum operating temperature	-30 °C
Maximum operating temperature	70 °C
Self-extinguishing fire class according to UL 94	HB

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39203000

COMPATIBILITY

Ribbon	TPPS-060 PREMIUM
Printable with	ROLLY3000

MATERIAL COMPOSITION AND TREATMENTS

Material	Styrene-Butadiene-Styrene STS
Silicone-free	Yes
Halogen free	Yes

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

ETF-ROLL-SBS

tipo	Colour	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
44132-SBS	Orange	235	5	13	57	35	11	0,639	4400
44162-SBS	Blue	235	5	13	57	35	11	0,647	4400
44112-SBS	Black RAL 9005	235	5	13	57	35	11	0,645	4400
44122-SBS	Rosso	235	5	13	57	35	11	0,643	4400
44152-SBS	Green	235	5	13	57	35	11	0,639	4400
44192-SBS	White	235	5	13	57	35	11	0,643	4400
44142-SBS	Yellow	235	5	13	57	35	11	0,645	4400
44193-SBS	White	200	2	25	100	75	23	2,750	4401
44143-SBS	Yellow	200	2	25	100	75	23	2,715	4401
44153-SBS	Green	200	2	25	100	75	23	2,588	4401
44123-SBS	Rosso	200	2	25	100	75	23	2,588	4401
44113-SBS	Black RAL 9005	200	2	25	100	75	23		4401
44163-SBS	Blue	200	2	25	100	75	23	2,525	4401
44183-SBS	Grey	200	2	25	100	75	23		4401
44495-SBS	White	333	3	20	65	38	18	1,180	4402
44425-SBS	Rosso	333	3	20	65	38	18	1,158	4402
44435-SBS	Orange	333	3	20	65	38	18	1,191	4402
44455-SBS	Green	333	3	20	65	38	18	1,191	4402
44494-SBS	White	166	3	20	125	18	98	2,144	4403