

TPM-ROLL



Features

TECHNICAL INFORMATION

Minimum operating temperature	-30 °C
Maximum operating temperature	60 °C
Self-extinguishing fire class according to UL 94	V0

WEIGHT AND DIMENSIONS

Width	4 mm
Base of the printable area	4 mm

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

MATERIAL COMPOSITION AND TREATMENTS

Material	Rigid PVC
Silicone-free	No
Halogen free	No

LOGISTIC

Storage temperature	10 ÷ 25 °C
Relative humidity of storage	45 ÷ 55
Customs code	39204910

COMPATIBILITY

Ribbon	TPS-060
Printable with	ROLLY3000

TPM-ROLL

tipo	Colour	Number of lines	Number of columns	L [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
44092B	White	1040	12	15	15	0,083	4023
44091B	White	1040	12	12	12	0,084	4022
44090B	White	1360	12	10	10	0,066	4020
44096B	White	570	11	30	30	0,155	4026
44093B	White	850	12	20	20	0,098	4025
44097B	White	455	11	40	40	0,200	4007
44042B	Yellow	1040	12	15	15	0,085	4023
44041B	Yellow	1040	12	12	12	0,081	4022
44040B	Yellow	1360	12	10	10	0,067	4020
44046B	Yellow	570	11	30	30	0,157	4026
44043B	Yellow	850	12	20	20	0,095	4025
44047B	Yellow	455	11	40	40	0,194	4007

