

MG-KMP

ADHESIVE CABLE MARKERS, ON SHEETS, PRE-CUT, IN POLYOLEFIN, SILICONE FREE, HALOGEN FREE



CERTIFICATIONS & APPROVALS

UL (cURus)

Features

TECHNICAL INFORMATION

Minimum operating temperature	-70 °C
Maximum operating temperature	140 °C
Minimum application temperature	10 °C
Maximum application temperature	40 °C
Type of adhesive	solvent acrylic adhesive film
Self-extinguishing fire class according to UL 94	NA

MATERIAL COMPOSITION AND TREATMENTS

Material	Polyolefin PO99006TR
Silicone-free	Yes
Halogen free	Yes

LOGISTIC

Storage temperature	10 ÷ 25 °C
Duration of storage	720 d
Relative humidity of storage	45 ÷ 55
Customs code	39199080

CLASSIFICATION AND DATA ORDERING

ETIM Class 7	Labelling material [EC001288]
--------------	-------------------------------

COMPATIBILITY

Ribbon	MG2-ETR
Printable with	MG3; MG4
Plates	MG2-PLT

MG-KMP019

Range of cable housing diameter
2 ÷ 3 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49962-013	White	30	6	5	13	19	13	9	0,107	392
49462-013	Yellow	30	6	5	13	19	13	9	0,109	392

MG-KMP025

Range of cable housing diameter
2.6 ÷ 4.1 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49956-015	White	24	6	4	15	25	15	9	0,136	393
49456-015	Yellow	24	6	4	15	25	15	9	0,136	393
49956-023	White	16	4	4	23	25	23	9	0,204	394
49456-023	Yellow	16	4	4	23	25	23	9	0,205	394

MG-KMP038

Range of cable housing diameter
4.3 ÷ 7 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49950-015	White	18	6	3	15	38	15	10	0,192	381
49450-015	Yellow	18	6	3	15	38	15	10	0,192	381
49950-023	White	12	4	3	23	38	23	10	0,288	382
49450-023	Yellow	12	4	3	23	38	23	10	0,292	382

MG-KMP050

Range of cable housing diameter
6 ÷ 10 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49951-012	White	14	7	2	15	50	15	12	0,219	383
49951-015	White	12	6	2	15	50	15	15	0,258	384
49451-015	Yellow	12	6	2	15	50	15	15	0,260	384
49951-023	White	8	4	2	23	50	23	15	0,388	385
49451-023	Yellow	8	4	2	23	50	23	15	0,393	385

MG-KMP062

Range of cable housing diameter
6.5 ÷ 12 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49958-012	White	14	7	2	12	62	12	18	0,251	395
49458-012	Yellow	14	7	2	12	62	12	18	0,251	395

MG-KMP068

Range of cable housing diameter
7 ÷ 13 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49959-040	White	4	2	2	22	68	22	40	0,930	396
49459-040	Yellow	4	2	2	22	68	22	40	0,930	396

MG-KMP075

Range of cable housing diameter
8 ÷ 14 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49952-015	White	6	6	1	15	75	15	25	0,427	386
49452-015	Yellow	6	6	1	15	75	15	25	0,427	386
49952-023	White	4	4	1	23	75	25	23	0,640	387
49452-023	Yellow	4	4	1	23	75	23	25	0,640	387

MG-KMP080

Range of cable housing diameter
10 ÷ 17 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49964-047	White	2	2	1	47	80	47	25	1,360	397
49464-047	Yellow	2	2	1	47	80	47	25	1,350	397

MG-KMP082

Range of cable housing diameter
10.5 ÷ 18 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49954-050	White	2	1	2	50	82	50	25	1,390	388

MG-KMP092

Range of cable housing diameter
11 ÷ 19 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49965-080	White	1	1	1	80	92	80	20	2,820	398
49465-080	Yellow	1	1	1	80	92	80	20	2,820	398

MG-KMP100

Range of cable housing diameter
12 ÷ 20 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49953-015	White	6	6	1	15	100	15	25	0,507	389
49453-015	Yellow	6	6	1	15	100	15	25	0,510	389
49953-023	White	4	4	1	23	100	23	25	0,765	390
49453-023	Yellow	4	4	1	23	100	23	25	0,775	390

MG-KMP135

Range of cable housing diameter
20 ÷ 25 mm

tipo	Colour	Sheet elements	Number of lines	Number of columns	Width [mm]	L [mm]	Base of the printable area [mm]	Height of the printable area [mm]	Gross weight [g]	Software code
49455-050	Yellow	2	2	1	50	135	50	50	1,970	391
49555-050	Green	2	2	1	50	135	50	50	1,980	391
49955-050	White	2	2	1	50	135	50	50	1,950	391