

## PMF-HF

FLAT HOLDERS, FOR FLAT TAGS, EVA COPOLYMER, HALOGEN FREE



## Features

### TECHNICAL INFORMATION

Minimum operating temperature	-40 °C
Maximum operating temperature	80 °C
Colour	Transparent
Self-extinguishing fire class according to UL 94	HB

### MATERIAL COMPOSITION AND TREATMENTS

Material	Copolymer EVA
Silicone-free	No
Halogen free	Yes

### LOGISTIC

Customs code	39269097
--------------	----------

**PMF-00-HF** Range of cable housing diameter **1.3 ÷ 2.2 mm** Range of cable cross section **0.25 ÷ 0.5 mm<sup>2</sup>**

tipo	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90000-HF	4.8	10	0,106	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90010-HF	4.8	12	0,127	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90020-HF	4.8	15	0,154	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90040-HF	4.8	20	0,186	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]

**PMF-01-HF** Range of cable housing diameter **2 ÷ 3.7 mm** Range of cable cross section **0.5 ÷ 2.5 mm<sup>2</sup>**

tipo	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90100-HF	5	10	0,144	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90110-HF	5	12	0,180	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90120-HF	5	15	0,213	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90140-HF	5	20	0,279	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90170-HF	4	30	0,600			Labelling material [EC001288]

**PMF-02-HF** Range of cable housing diameter **3.4 ÷ 4.3 mm** Range of cable cross section **2.5 ÷ 4 mm<sup>2</sup>**

tipo	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90200-HF	5.1	10	0,185	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90210-HF	5.1	12	0,218	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90220-HF	5.1	15	0,281	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90240-HF	5.1	20	0,438	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90270-HF	5.1	30		10 ÷ 25	45 ÷ 55	Labelling material [EC001288]

**PMF-03-HF** Range of cable housing diameter **4 ÷ 6.3 mm** Range of cable cross section **4 ÷ 10 mm<sup>2</sup>**

tipo	Width [mm]	L [mm]	Gross weight [g]	Storage temperature [°c]	Relative humidity of storage	ETIM Class 7
90300-HF	7.6	10	0,267	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90310-HF	7.6	12	0,314	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90320-HF	7.6	15	0,358	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90340-HF	7.6	20	0,600	10 ÷ 25	45 ÷ 55	Cable coding system [EC001530]
90370-HF	4	30	0,915			Labelling material [EC001288]

